

WEST 1/4 CORNER SECTION 10, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 234 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 10-20-10 ON JUNE 19, 1857.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 28" X 15" X 1-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-10
 - 2) 40.00 CHAINS SOUTH TO THE 33" X 7" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-20-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 82 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 139 DATED AUGUST 15, 1875 TO ESTABLISH THE CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 3-20-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 10-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION
 - 1) 2,638' NORTH TO THE 34" X 8" X 6" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 10-20-10
 - 2) 5,276' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-20-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 268 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 22 TO 24 [PACKET 517 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT PETITIONED BY J. Y. SCHOECK AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 19-10 AND 20-10 THAT HE SURVEYED ON JUNE 16, 1884, APPARENTLY **FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 3-20-10 ON THIS ROAD SURVEY AS THE TERMINUS OF THE PART ALLOWED ON THIS ROAD SURVEY WAS AT THIS CORNER.
HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:
 - 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 27, TOWNSHIP 19, RANGE 12, I RAN SOUTH ON THE SECTION LINES BETWEEN SECTIONS 27 & 28, 33 & 34 TO THE TOWNSHIP LINE; THENCE SOUTH IN TOWNSHIP 20, RANGE 10 BETWEEN SECTIONS 3 & 4 AND 9 & 10 TO THE TERMINUS OF THIS ROAD SURVEY.
 - 2) THE VIEWERS REPORTED IN FAVOR OF ALLOWING SAID ROAD AS A PUBLIC NECESSITY.
 - 3) THE VIEWERS DETERMINED THAT IF SAID ROAD BE GRANTED THAT ITS WIDTH SHALL BE FIFTY (50) FEET.
 - 4) THE FINAL ORDER BY THE BOARD OF COUNTY COMMISSIONERS ON PAGE 24 SAID THAT THE ROAD IS LOCATED FROM THE PLACE OF BEGINNING TO THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 3, TOWNSHIP 20, RANGE 10 [THE LAST ONE-HALF MILE WAS **NOT** ALLOWED] AS NOTED ON JULY 12, 1884 BY JOHN L. BUTLER, CHAIRMAN PRO-TEM OF THE COMMISSION AND ATTESTED BY ROLAND LAKIN, COUNTY CLERK.

- 4) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, FOR R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 125, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 125 DATED OCTOBER 23 & 24, 1885 ORDERED BY H. C. WOOD TO SURVEY SECTIONS 9 & 10-20-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 9-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1,322' WEST TO THE LARGE LIMESTONE HE FOUND AS IT LAY SOLID IN THE NATURAL GROUND AND HE MARKED FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NE1/4 OF SECTION 9-20-10
 - 2) 2,643.5' WEST TO THE NORTH & SOUTH 1/4 SECTION LINE IN SECTION 9-20-10
 - 3) 1,320' EAST TO THE LIMESTONE 8" X 6" IN BASE, 5" IN THE CENTER, THIN AT THE TOP AND 18" LONG, HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NW1/4 OF SECTION 10-20-10
 - 4) 5,240' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 10-20-10
- 5) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 19, 2015, FOR PROJECT NUMBER 15181-02, THE SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 10-20-10 FOR LAMBERT/DOTY, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 20-10, SAID THAT HE EXCAVATED WITH A COUNTY BACKHOE FOR THE STONE OF RECORD AT THE WEST 1/4 CORNER OF SECTION 10-20-10. **HE FOUND THE 25" X 7" X 6" LIMESTONE LEANED OVER ± 18" DEEP. HE STOOD THE STONE UPRIGHT AND HE SET A 5/8" X 6" IRON PIN WITH A LYON COUNTY CAP OVER THE TOP OF THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-20-10.**
- 1) 1/2" X 24" IRON WITH "PS 752" CAP SET ON THE NORTH SIDE CENTER AND FLUSH WITH THE TOP OF THE STONE
 - 2) 23.0' WEST TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A CORNER FENCE POST
 - 3) 26.95' NE TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF THE NORTH GATE POST
 - 4) 24.38' SE TO THE TOP CENTER OF A 24" STEEL CULVERT PIPE [**HORIZONTAL TIE**]
 - 5) 23.25' SW TO THE TOP CENTER OF A 24" STEEL CULVERT PIPE [**HORIZONTAL TIE**]
 - 6) 46.6' NW TO THE TOP OF A GAS PIPE POST
 - 7) 1.0' SOUTH TO A FENCE TO THE WEST
 - 8) 2' SOUTH TO A FENCE TO THE EAST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,641.32' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 10-20-10
 - 2) 2,647.97' SOUTH TO THE 1/2" SQUARE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 10-20-10
 - 3) 781.00' ± TO THE CORNER BETWEEN THE WEST TRACT AND THE EAST TRACT
 - 4) 2,617.12' EAST TO THE 5/8" X 24" ION PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 10-20-10
 - 5) 5,248.10' EAST TO THE SONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 10-20-10

WEST QUARTER CORNER 10-20-10