

NORTH 1/4 CORNER SECTION 14, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 230 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 14-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.88 CHAINS WEST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-20-10
 - 2) 39.86 CHAINS EAST TO THE 24" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-20-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 65 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 213 DATED AUGUST 5, 1872 TO ESTABLISH THE CORNERS OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 14-20-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 14-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,642-1/2' SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-20-10
 - 2) 5,285' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 14-20-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 74 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 131 DATED JULY 1, 1875 TO DIVIDE THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 11-20-10 BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTIONS 11-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,317' WEST TO THE 18" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF THE SW1/4 OF SECTION 11-20-10
 - 2) 2,634' WEST TO THE STONE HE FOUND AND **HE RESET** FOR THE SOUTHWEST CORNER OF SECTION 11-20-10

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 23, 1989, FOR JOB NUMBER 89027, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 11-20-10 WAS **LOST**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 11-20-10.
 - 1) 5.25' WNW TO A NAIL & WASHER IN A WOOD BOX CULVERT SUPPORT POST
 - 2) 8.8' WNW TO A NAIL & WASHER IN A WOOD BOX CULVERT SUPPORT POST
 - 3) 16.3' NNW TO A NAIL & WASHER IN A WOOD BOX CULVERT SUPPORT POST
 - 4) 18.65' NNE TO A NAIL & WASHER IN A WOOD BOX CULVERT SUPPORT POST
 - 5) 24.5' SOUTH TO AN EAST-WEST FENCE LINE
 - 6) 1.0' NORTH TO THE SOUTH EDGE OF A WOOD BOX CULVERT

NORTH QUARTER CORNER 14-20-10