

WEST 1/4 CORNER SECTION 14, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 229 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 15-20-20.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 65 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 213 DATED AUGUST 5, 1872 TO ESTABLISH THE CORNERS OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 14-20-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 14-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,315-1/2' EAST TO THE 12" X 8" X 2" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 14-20-10
 - 2) 2,631' EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-20-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 74 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 131 DATED JULY 1, 1875 TO DIVIDE THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 11-20-10 BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 14-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 2,641-1/2' NORTH TO THE ORIGINAL STONE HE FOUND AND **HE RESET** FOR THE SOUTHWEST CORNER OF SECTION 11-20-10
 - 2) 5,283' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 11-20-10

WEST QUARTER CORNER 14-20-10