

NORTH 1/4 CORNER SECTION 15, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 234 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 19" X 1-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 15-20-10 ON JUNE 19, 1857. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.85 CHAINS WEST TO THE 33" X 7" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-20-10
 - 2) 39.85 CHAINS EAST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-20-10

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 78 DATED AUGUST 20, 1947, TO LOCATE THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 15-20-10, SAID THAT **HE SET A TEMPORARY POINT** FOR THE NORTH 1/4 CORNER OF SECTION 15-20-10 IN LINE WITH A FENCE FUNNING SOUTH ON THE 1/2 SECTION LINE ON THIS **INFORMAL SURVEY**. HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,306.0' WEST TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 15
 - 2) 2,612.0' WEST TO THE TEMPORARY POINT HE SET FOR THE NORTHWEST CORNER OF SECTION 15-20-10, IN THE CENTER OF A 49.5' ROAD RUNNING EAST ON THE SECTION LINE AND A FENCE RUNNING WEST
 - 3) 1,324.1' SOUTH TO THE TEMPORARY POINT HE SET FOR THE EAST 1/8TH CORNER OF THE NW1/4 OF SECTION 15-20-10
 - 4) 2,648.3' SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 15-20-10

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 24, 1998, FOR JOB NUMBER 98161-02, SAID THAT **HE FOUND BROKEN PIECES OF LIMESTONE** AT THE SOUTH 1/4 CORNER OF SECTION 10-20-10 SIMILAR TO THE USUAL GLO STONE THAT HE FOUND IN THE AREA. **HE DROVE A 5/8" REBAR WITH A LYON COUNTY CAP THROUGH THE CENTER OF THE LIMESTONE PIECES** FOR THE SOUTH 1/4 CORNER OF SECTION 10-20-10.
 - 1) 24.20' SOUTH TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
 - 2) 33.0' SW TO A 40 D NAIL & WASHER IN A 0.5' WALNUT TREE
 - 3) 31.30' NORTH TO AN EAST-WEST FENCE
 - 4) IN LINE WITH A FENCE TO THE SOUTH
 - 5) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROADHIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
 - 1) 2,611.44' WEST TO THE SQUARE #5 REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 10-20-10
 - 2) 2,629.27' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-20-10

- 4) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 19, 2015, FOR PROJECT NUMBER 15181-02, THE SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 10-20-10 FOR LAMBERT/DOTY, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 20-10, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" IRON PIN WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 10-20-10 FROM HIS DIES DATED IN 1998 FOR PROJECT 98161 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE. **[NOTE:** HIS 1998 TIES INDICATED THAT HE DROVE THIS CAPPED REBAR THRU THE

CENTER OF THE LIMESTONE PIECES THAT HE FOUND AT THIS CORNER. WARREN
CHIP WOODS, P.S. 603, COUNTY SURVEYOR]

- 1) 29.30' SE TO THE TOP CENTER OF A PIPE GATE POST
- 2) 33.00' SW TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF THE WEST GATE
POST
- 3) 24.20' SOUTH TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 4) 31.30' NORTH TO A LINE OF FENCE TO THE EAST AND WEST
- 5) 1.50' WEST TO A LINE OF FENCE TO THE SOUTH
- 6) 1.50' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF GRAVEL
COUNTY ROAD 110 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,611.38' WEST TO THE 1/2" SQUARE IRON PIN HE FOUND AT THE SOUTHWEST
CORNER OF THE SW1/4 OF SECTION 10-20-10
- 2) 2,644.44' NORTH TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET
FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 10-20-10
- 3) 5,285.94' NORTH TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE
RESET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 10-20-10

NORTH QUARTER CORNER 15-20-10