

NORTH 1/4 CORNER SECTION 22, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 233 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 31" X 20" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-20-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.96 CHAINS WEST TO THE 31" X 9" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-20-10
 - 2) 39.95 CHAINS EAST TO THE 22" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-20-10
- 2) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 25, 2011 FOR PROJECT NUMBER 11086-02, SURVEY F15001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF THE SOUTH LINE OF THE SOUTHEAST QUARTER OF SECTION 15-20-13 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR LYON COUNTY PROJECT 10-XA, THE REPLACEMENT OF BRIDGE 931.7-534.0, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE OF RECORD AT THE SOUTH 1/4 CORNER OF SECTION 15-20-10, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 15-20-10 BY THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, I.E., IN LINE WITH THE FENCES TO THE NORTH AND SOUTH AND AT A SPLIT OF THE RIGHT-OF-WAY FENCES FOR COUNTY ROAD 100. THIS SECTION CORNER IS ALSO PROJECT STATION 0+00.00.
- 1) 28.0' SE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 27.25' NE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 3) 24.85' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 4) 37.3' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 80.35' SW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 6) IN LINE WITH THE FENCES TO THE NORTH AND SOUTH EXTENDED
 - 7) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 100 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 704.82' EAST TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR P.O.T. STATION 7+04.82
 - 2) 1,304.82' EAST TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR P.O.T. STATION 13+04.83
 - 3) 2,638.58' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 15-20-10 AT P.O.T. STATION 26+38.58
 - 4) 5,274.52' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 14-20-10 AT P.O.T. STATION 52+74.52

NORTH QUARTER CORNER 22-20-10