

NORTH 1/4 CORNER SECTION 23, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 229 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-20-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.92 CHAINS WEST TO THE 22" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-20-10
- 2) 39.91 CHAINS EAST TO THE 25" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-20-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 65 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 213 DATED AUGUST 5, 1872 TO ESTABLISH THE CORNERS OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 14-20-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 14-20-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322-1/2' WEST TO THE 16" X 8" X 2-1/2" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 14-20-10
- 2) 2,645' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 14-20-10
- 3) 2,642-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-20-10
- 4) 5,285' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-20-10

- 2) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 25, 2011 FOR PROJECT NUMBER 11086-02, SURVEY F15001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF THE SOUTH LINE OF THE SOUTHEAST QUARTER OF SECTION 15-20-13 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR LYON COUNTY PROJECT 10-XA, THE REPLACEMENT OF BRIDGE 931.7-534.0, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE OF RECORD AT THE SOUTH 1/4 CORNER OF SECTION 14-20-10, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 14-20-10 BY THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, I.E., AT A SPLIT OF THE RIGHT-OF-WAY FENCES FOR ROAD 100, AND IN LINE WITH A FENCE TO THE NORTH. THIS SECTION CORNER IS P.O.T. STATION 52+74.52.

- 1) 31.4' NE TO A CONCRETE NAIL & WASHER IN THE EAST GATE POST
- 2) 24.9' NW TO A CONCRETE NAIL & WASHER IN THE WEST GATE POST
- 3) 27.15' SW TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 4) 29.0' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 5) IN LINE WITH A FENCE TO THE NORTH EXTENDED
- 6) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 100 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,635.94' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 15-20-10 AT P.O.T. STATION 26+38.58
- 2) 3,969.70' WEST TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR P.O.T. STATION 13+04.82
- 3) 4,569.70' WEST TO THE 1/2" REBAR WITH HIS "LS 1368" CAP HE SET FOR P.O.T. STATION 7+04.82

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 5,274.52' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 15-20-10 AT P.O.T. STATION 0+00.00

NORTH QUARTER CORNER 23-20-10