

WEST 1/4 CORNER SECTION 25, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 225 OF THE GLO ORIGINAL FILED NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 26-20-10.

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT HE DUG FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 26-20-10, BUT HE DID **NOT** FIND THE STONE. **HE SET A 1/2" DIAMETER IRON PIN** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-20-10 ON LINE AND HALFWAY BETWEEN THE 1/2" DIAMETER IRON PIN THAT HE SET FOR AT THE PERMANENT NORTHEAST CORNER OF SECTION 26-20-10 AND THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 26-20-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,642.5' NORTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 26-20-10
 - 2) 2,642.5' SOUTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 26-20-10
 - 3) 7,922.5' SOUTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 35-20-10 ON THE 4TH STANDARD PARALLEL
 - 4) 1,319.0' WEST TO THE 1/2" DIAMETER IRON PIN HE FOR THE PERMANENT NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-20-10
 - 5) 2,638.0' WEST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-10
 - 6) 5,276.0' WEST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 26-20-10

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS AN **IRON PIN** AT THE "W1/4 CORNER SECTION 25-10-10".
 - 1) 26.6' WEST TO AN OLD CORNER POST
 - 2) 29.6' NE TO THE NORTH GATE POST
 - 3) 21.9' EAST TO THE CORNER OF A HEDGE TREE

- 4) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 82 AT THE TOP OF THE PAGE SHOWS AN **IRON PIN** AT THE "E1/4 CORNER SECTION 26-20-10".
 - 1) 26.5' TO THE NEAR FACE OF AN OLD CORNER FENCE POST
 - 2) 29.6' NE TO THE NEAR FACE OF THE NORTH GATE POST
 - 3) 21.9' EAST TO THE NEAR CORNER OF A HEDGE TREE

- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 20, 1985, FOR PROJECT NUMBER 85014, SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF THE NORTH 30 ACRES OF THE SOUTHWEST QUARTER OF SECTION 25-20-10 RECORDED IN VOLUME 413 ON PAGE 675 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 20, 1985, SAID THAT **HE FOUND A 1/2" REBAR AT 3" DEEP** AT THE WEST 1/4 OF SECTION 25-20-10 ATTRIBUTABLE TO LESLIE M. GOULD IN PERMANENT SURVEY BOOK 1 ON PAGE 140.
 - 1) 2.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 2) 22.0' EAST TO A HEDGE LINE TO THE SOUTH
 - 3) 32.0' WEST TO THE NORTH & SOUTH FENCE LINE
 - 2) IN LINE WITH HEDGES TO THE EAST & WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,650.17' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 25-20-10
- 2) 493.18' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NORTH 30 ACRES OF THE SW1/4 OF SEC. 25-20-10
- 3) 2,643.13' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-20-10, ATTRIBUTABLE TO L. M. GOULD IN PERMANENT SURVEY BOOK 1 ON PAGE 140

- 6) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F25002 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR THE SURVEY OF A 7.9 ACRE TRACT LOCATED IN THE SOUTHWEST QUARTER OF SECTION 25-20-10 FOR PROJECT NUMBER 86071 DATED JULY 30, 1986, AND RECORDED IN VOLUME 427 ON PAGE 31 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 20, 1986, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 1/2" REBAR ATTRIBUTABLE TO L. M. GOULD** AT THE WEST 1/4 CORNER OF SECTION 25-20-10. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES. **[NOTE: THIS 1/2" REBAR WAS SET BY THE PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 140 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,313.13' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 7.9 ACRE TRACT
- 2) 2,643.13' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-20-10, ATTRIBUTABLE TO L. M. GOULD

WEST QUARTER CORNER 25-20-10