

CENTER CORNER OF SECTION 26, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT **HE SET A 1/2" DIAMETER IRON PIN** FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE QUARTER CORNERS ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,638.0' WEST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 26-20-10
 - 2) 1,319.0' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-20-10
 - 3) 2,638.0' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-20-10

- 2) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 80 AT THE BOTTOM OF THE PAGE SHOWS A **1/2" SQUARE IRON PIN** AT THE "CENTER CORNER SECTION 26-20-10" ON AUGUST 1, 1946.
 - 1) 4.0' NW TO THE NEAR FACE OF A CORNER FENCE POST
 - 2) 3.0' SOUTH OF AN EAST-WEST FENCE
 - 3) 3.3' EAST OF A NORTH-SOUTH FENCE

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS AN **IRON PIN** AT THE "C1/4 CORNER SECTION 26-20-10".
 - 1) 35.2' SW TO A FENCE POST
 - 2) 17.2' NE TO A FENCE POST
 - 3) 3' SOUTH OF A LINE FENCE
 - 4) 3.3' EAST OF A LINE FENCE
 - 5) 4' SOUTH OF A CORNER FENCE POST

CENTER CORNER 26-20-10