

NORTH 1/16TH CORNER OF THE SOUTHEAST QUARTER OF SECTION 26, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT **HE SET A 1/2" DIAMETER IRON PIN** FOR THE PERMANENT NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 26-20-10 ON LINE AND HALFWAY BETWEEN THE 1/2" DIAMETER IRON PIN THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-10 AND THE 1/2" DIAMETER IRON PIN THAT HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-20-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.0' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-20-10
 - 2) 1,319.0' WEST TO THE 1/2" DIAMETER IRON PIN SET FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-10
 - 3) 3,957.0' WEST TO THE 1/2" DIAMETER IRON PIN SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 26-20-10
- 2) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS AN **IRON PIN** AT THE "SW CORNER SE1/4 NE1/4 SECTION 26-20-10". THERE ARE NO TIES ON THIS PAGE.

NORTH SIXTEENTH CORNER OF SOUTHEAST QUARTER 26-20-10