

WEST 1/4 CORNER SECTION 26, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 228 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-20-10.

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT HE DUG FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 26-20-10, BUT HE DID **NOT** FIND THE STONE. **HE SET A 1/2" DIAMETER IRON PIN** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 26-20-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 26-20-10 AND THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 26-20-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.5' NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 26-20-10
 - 2) 2,646.5' SOUTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 26-20-10
 - 3) 7,939.5' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 35-20-10 ON THE 4TH STANDARD PARALLEL
 - 4) 2,638.0' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-10
 - 5) 3,957.0' EAST TO THE 1/2" DIAMETER IRON PIN SET FOR THE PERMANENT NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-20-10
 - 6) 5,276' EAST TO THE 1/2" DIAMETER IRON PIN SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-20-10

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS AN **IRON PIN** AT THE "E1/4 CORNER SECTION 27-20-10".
 - 1) 35.2' WSW TO A STONE FENCE POST
 - 2) 17.2' NE TO A CORNER FENCE POST

- 4) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 82 AT THE BOTTOM OF THE PAGE SHOWS AN **IRON PIN** AT THE "W1/4 CORNER SECTION 26-20-10".
 - 1) 35.2' WSW TO THE NEAR CORNER OF A STONE FENCE POST
 - 2) 17.2' ENE TO THE NEAR FACE OF A CORNER FENCE POST

WEST QUARTER CORNER 26-20-10