

NORTHWEST CORNER SECTION 33, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 235 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 12" X 6"** FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.13 CHAINS EAST TO THE 27" X 15" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-20-10
 - 2) 80.25 CHAINS EAST TO THE 30" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-20-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 60 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 242 TO 244 PETITIONED BY PHILLIP H. HORST AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-10 [PACKET 332 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 31, 1880, WAS ESTABLISHED AT A 50 FOOT WIDE ROAD ON APRIL 12, 1880, AND WAS RECORDED ON APRIL 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-20-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-10 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED JANUARY 30, 1880, FOR A COUNTY ROAD IN TOWNSHIP 20-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-20-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-10 TO COMMENCE THIS ROAD SURVEY

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 402 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 546 TO 548 PETITIONED BY E. J. RATCLIFF AND OTHERS FOR A ROAD IN TOWNSHIP 20-10 [PACKET 657 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 17, 1893, WAS ORDERED ESTABLISHED AS A 40 FOOT ROAD ON JANUARY 4, 1894 AS NOTED BY W. N. D. BIRD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY C. W. WILHITE, COUNTY CLERK, AND RECORDED ON JUNE 24, 1894 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT HE ENDED THIS ROAD SURVEY AT THE SOUTHEAST CORNER OF SECTION 29-20-10. HE DID NOT INDICATE IF HE FOUND OR SET A STONE FOR THIS CORNER.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND OR SET AT THE NORTHEAST CORNER OF SECTION 20-20-10 TO BEGIN THIS ROAD SURVEY, TAKING 20 FEET ON EACH SIDE OF THE

SECTION LINE **EXCEPT** THAT THE HEDGE ROW NEAR THE EAST LINE OF THE SE1/4 OF SECTION 29-20-10 SHALL BE CONSIDERED THE WEST LINE OF THE ROAD IF IT IS LESS THAN 20 FEET FROM THE SECTION LINE

NORTHWEST CORNER 33-20-10