

NORTHWEST CORNER SECTION 34, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 231 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 12" X 5"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.01 CHAINS EAST TO THE 29" X 17" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-20-10
 - 2) 80.02 CHAINS EAST TO THE 15" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-20-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 60 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 242 TO 244 PETITIONED BY PHILLIP H. HORST AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-10 [PACKET 332 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 31, 1880, WAS ESTABLISHED AT A 50 FOOT WIDE ROAD ON APRIL 12, 1880, AND WAS RECORDED ON APRIL 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-20-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-10 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED JANUARY 30, 1880, FOR A COUNTY ROAD IN TOWNSHIP 20-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-20-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-10 TO COMMENCE THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 118, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 118 FOR TWO ROADS IN TOWNSHIP 20-10 FOR BY H. C. WOOD, PRINCIPAL PETITIONER, DATED SEPTEMBER 8, 1885, **APPARENTLY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-20-10 ON THE SECOND ROAD ON THIS ROAD SURVEY.
[NOTE: THE SECOND ROAD FROM THE WEST 1/4 CORNER OF SECTION 3-20-10 SOUTH TO THE NORTHWEST CORNER OF SECTION 15-20-10 WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS – SEE ROAD RECORD BOOK "C" ON PAGES 186 TO 188 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE SECOND ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-20-10 TO BEGIN THIS ROAD SURVEY

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) THE SECOND ROAD EXTENDS SOUTH ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-20-10 ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 109 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 186 TO 188 PETITIONED BY H. C. WOOD AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-10 [PACKET 536 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A ROAD BEGINNING AT THE 1/4 CORNER ON THE WEST SIDE OF SECTION 3-20-10, THENCE SOUTH TO THE SOUTHWEST CORNER OF SECTION 34, SAME TOWN AND RANGE. HE BEGAN THIS ROAD SURVEY ON SEPTEMBER 8, 1885; IT WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FROM THE NORTHWEST CORNER OF SECTION 15-20-10 TO THE SOUTHWEST CORNER OF SECTION 34-20-10 ONLY ON OCTOBER 9, 1885 AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 20, 1886 BY ROLAND LAKIN, COUNTY CLERK. **HE APPARENTLY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-20-10 ON THE ROAD ALLOWED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE ROAD ALLOWED EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES AT 20 FEET EACH SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-20-10 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
- 2) THE ALLOWED ROAD EXTENDS SOUTH AT 20 FEET EACH SIDE OF THE SECTION LINES TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 34-20-20; THEN CONTINUES SOUTH WITH THE LAST HALF MILE LAID ON THE EAST SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-20-10 ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY
- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 406 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 554 TO 556 PETITIONED BY OSCAR DARR AND OTHERS FOR A ROAD IN TOWNSHIP 20-10 [PACKET 659 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 14, 1884, WAS ORDERED ESTABLISHED AS A 40 FOOT ROAD ON JULY 7, 1894 AS NOTED BY J. A. MILLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY C. W. WILHITE, COUNTY CLERK, AND RECORDED ON JUNE 26, 1895 BY MATTHEW BROWN, COUNTY SURVEYOR, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-20-10 ON THIS ROAD SURVEY THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 4-1/2 MILES TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-20-10 TO BEGIN THIS ROAD SURVEY, TAKING 20 FEET ON EACH SIDE OF THE SECTION LINES
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 33 & 35-20-10 ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY, TAKING 20 FEET ON EACH SIDE OF THE SECTION LINES
- 7) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR THE DESCRIPTION OF A 500 FOOT BY 1,400 FOOT TRACT IN THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 27-20-10 BUT NOT DATED, IT SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 27-20-10. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THERE IS NO**

DESCRIPTION OF THE MONUMENT OR THE METHODOLOGY HE USED TO DETERMINE THE LOCATION FOR THIS SECTION CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 500' NORTH ON THE SECTION LINE AND FENCE LINE TO THE "MONUMENT" HE SET FOR THE NORTHWEST TRACT CORNER – NOT DESCRIBED
- 2) 1,400' EAST ON THE SECTION LINE TO THE "MONUMENT" HE SET FOR THE SOUTHEAST TRACT CORNER – NOT DESCRIBED

NORTHWEST CORNER 34-20-10