

WEST 1/4 CORNER SECTION 34, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 231 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-20-10.
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 109 AND DATED MAY 1888, SAID THAT **HE SET A ROAD STONE MARKED "R" CLOSE BY THE EAST SIDE OF THE EXISTING STONE** AT THE WEST 1/4 CORNER OF SECTION 34-20-10, WITH THE WEST 1/4 CORNER BEING THE CENTER OF THE ROAD.
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 109 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 186 TO 188 PETITIONED BY H. C. WOOD AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-10 [PACKET 536 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A ROAD BEGINNING AT THE 1/4 CORNER ON THE WEST SIDE OF SECTION 3-20-10, THENCE SOUTH TO THE SOUTHWEST CORNER OF SECTION 34, SAME TOWN AND RANGE. HE BEGAN THIS ROAD SURVEY ON SEPTEMBER 8, 1885; IT WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FROM THE NORTHWEST CORNER OF SECTION 15-20-10 TO THE SOUTHWEST CORNER OF SECTION 34-20-10 ONLY ON OCTOBER 9, 1885 AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 20, 1886 BY ROLAND LAKIN, COUNTY CLERK. **HE APPARENTLY FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-20-10 ON THE ROAD ALLOWED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE ROAD ALLOWED EXTENDS NORTH ON THE SECTION LINES FOR 3-1/2 MILES AT 20 FEET EACH SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-20-10 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
 - 2) THE ALLOWED ROAD EXTENDS SOUTH WITH THE LAST HALF MILE LAID ON THE EAST SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-20-10 ON THE 4TH STANDARD PARALLEL TO THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY
- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 25, 1985, FOR JOB NUMBER 85104, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A 3.2 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 33-20-10 RECORDED IN VOLUME 419 ON PAGE 521 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 27, 1985, SAID THAT EXCAVATION WITH A COUNTY BACKHOE OVER A WIDE AREA **FAILED TO PRODUCE THE STONE** OF RECORD AT THE EAST 1/4 CORNER OF SECTION 33-20-10. HE DEEMED THAT THIS CORNER WAS **OBLITERATED.** **HE SET A 3/4" X 20" GAS PIPE** FOR THE EAST 1/4 CORNER OF SECTION 33-20-10 IN THE CENTER OF THE 40 FOOT ROAD AND IN LINE WITH A FENCE TO THE WEST AND THE APPARENT REMAINS OF A FENCE TO THE EAST. HE SAID IN HIS *REPORT OF SURVEY* THAT THIS POSITION IS SUPPORTED BY THE PHYSICAL EVIDENCE OF THE NORTHEAST CORNER OF SECTION 34-20-10 AND THE SOUTHEAST CORNER OF SECTION 34-20-10 ON THE 4TH STANDARD PARALLEL AS RE-ESTABLISHED.
 - 1) 47.3' SSW TO THE NEAR FACE OF A 5" GATE PIPE POST
 - 2) 23.0 WEST TO THE NORTH FENCE LINE
 - 3) 1.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,022.7' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 3.2 ACRE TRACTHIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,272.7' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 3.2 ACRE TRACT
- 3) 2,637.7' SOUTH TO THE 4' STEEL "T" POST HE SET FOR THE SOUTHEAST CORNER OF SECTION 33-20-10 ON THE 4TH STANDARD PARALLEL

WEST QUARTER CORNER 34-20-10