

**NORTH 1/4 CORNER SECTION 35, TOWNSHIP 20 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 228 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 14" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-20-10.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.99 CHAINS WEST TO THE 15" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-20-10
  - 2) 39.99 CHAINS EAST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-20-10
  
- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT HE DUG FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 26-20-10, BUT HE DID **NOT** FIND THE STONE. **HE SET A 1/2" DIAMETER IRON PIN** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 26-20-10 ON LINE AND HALFWAY BETWEEN THE 1/2" DIAMETER IRON PIN THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 26-20-10, AND THE 1/2" DIAMETER IRON PIN THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 26-20-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,639.5' WEST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 26-20-10
  - 2) 1,319.25' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-20-10 [**NOTE:** THIS SHOULD BE **1,319.75'** TO BE HALFWAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
  - 3) 2,639.5' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 26-20-10
  
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS AN **IRON PIN** AT THE "N1/4 CORNER SECTION 35-20-10".
  - 1) 29.8' NW TO THE WEST GATE POST
  - 2) 36.0' NE TO A CORNER FENCE POST
  - 3) 39.0' SE TO AN IRON PIN
  
- 4) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 78 AT THE BOTTOM OF THE PAGE SHOWS AN **IRON PIN** AT THE "S1/4 CORNER SECTION 26-20-10".
  - 1) 29.8' WEST TO THE NEAR FACE OF THE WEST GATE POST
  - 2) 36.0' NE TO THE NEAR FACE OF A CORNER FENCE POST
  - 3) 39.0' SE TO AN IRON PIN

NORTH QUARTER CORNER 35-20-10