

NORTHWEST CORNER SECTION 35, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 228 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 15" X 2-1/2"** FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.99 CHAINS EAST TO THE 24" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-20-10
 - 2) 79.98 CHAINS EAST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-20-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 60 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 242 TO 244 PETITIONED BY PHILLIP H. HORST AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-10 [PACKET 332 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 31, 1880, WAS ESTABLISHED AT A 50 FOOT WIDE ROAD ON APRIL 12, 1880, AND WAS RECORDED ON APRIL 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 4 MILES TO THE NORTHWEST CORNER OF SECTION 31-20-10 ON THE RANGE LINE AND THE STONE HE FOUND AT THE LYON AND CHASE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-10 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED JANUARY 30, 1880, FOR A COUNTY ROAD IN TOWNSHIP 20-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 4 MILES TO THE NORTHWEST CORNER OF SECTION 31-20-10 ON THE RANGE LINE AND THE STONE HE FOUND AT THE LYON AND CHASE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-10 TO COMMENCE THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 179, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 179 DATED AUGUST 22, 1887 WITH NO PETITIONER NAMED FOR A COUNTY ROAD IN TOWNSHIP 20-10, **APPARENTLY FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 34-20-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-20-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-20-10 ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY.
 - 3) **NOTE:** SEE ROAD RECORD BOOK "C" ON PAGE 376 – THE BOARD OF COUNTY COMMISSIONERS **REJECTED** THE LAST 1/2 MILE OF ROAD BETWEEN THE EAST 1/4 CORNER OF SECTION 33-20-10 SOUTH TO THE SOUTHEAST CORNER OF

SECTION 33-20-10 ON THE 4TH STANDARD PARALLEL – WARREN CHIP WOODS,
L.S. 603, COUNTY SURVEYOR

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 356 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 374 TO 376 PETITIONED BY JOSEPH WAGNER AND OTHERS FOR A ROAD COMMENCING AT THE NORTHEAST CORNER OF SECTION 27-17-10, THENCE SOUTH ON THE SECTION LINES FOR 2 MILES TO THE SOUTHEAST CORNER OF SECTION 34-20-10 [PACKET 606 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 22, 1887, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 34-20-10. ON JANUARY 5, 1887 THE BOARD OF COUNTY COMMISSIONERS APPROVED A 40 FOOT WIDE ROAD FOR THE FIRST 1-1/2 MILES AND THE BALANCE OF THE ROAD WAS **REJECTED** AS NOTED BY T. E. McMILLAN, CHAIRMAN, AND RECORDED ON JANUARY 19, 1887 BY ROLAND LAKIN, COUNTY CLERK.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ALLOWED ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-20-10 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
- 2) THIS ALLOWED ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1/2 MILE TO THE EAST 1/4 CORNER OF SECTION 34-10-10 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY

- 6) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT HE DUG FOR THE STONE AT THE SOUTHWEST CORNER OF SECTION 26, BUT HE DID **NOT** FIND THE STONE. **HE SET A 1/2" DIAMETER IRON PIN** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 26-20-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 26-20-10 AND THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 35-20-10 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,293.0' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 35-20-10 ON THE 4TH STANDARD PARALLEL
 - 2) 2,645.0' NORTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 26-20-10
 - 3) 5,293.0' NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 26-20-10
 - 4) 2,639.5' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 26-20-10
 - 5) 3,958.75' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 26-20-10 [**NOTE:** BY CALCULATION THIS SHOULD BE 3,959.25' TO PLACE THIS CORNER HALF WAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 6) 5,279.0' EAST TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 26-20-10
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS AN **IRON PIN** AT THE "SE CORNER SECTION 27-20-10".
TIES ARE ON PAGE 3

- 1) 27.2' SW TO A STONE CORNER FENCE POST
 - 2) 35.5' SE TO A COTTONWOOD TREE
 - 3) 37.3' NE TO CORNER FENCE POST
- 8) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 80 AT THE TOP OF THE PAGE SHOWS AN **IRON PIN** AT THE "SW CORNER SECTION 26-20-10".
- 1) 27.2' SW TO THE NEAR FACE OF A STONE CORNER FENCE POST
 - 2) 35.5' SE TO THE NEAR FACE OF A TREE
 - 3) 37.3' NE TO THE NEAR FACE OF A CORNER FENCE POST

NORTHWEST CORNER 35-20-10