

NORTH 1/4 CORNER SECTION 36, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 224 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.08 CHAINS WEST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-20-10
 - 2) 40.08 CHAINS EAST TO THE 24" X 12" 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36-20-10 ON THE EAST TOWNSHIP BOUNDARY

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT HE DUG FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 36-20-10, BUT HE DID **NOT** FIND THE STONE. HE DID **NOT** RESET THE NORTH 1/4 CORNER OF SECTION 36-20-10 ON THIS **PERMANENT SURVEY**.

- 3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 9, 1984, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 36-20-10, BUT THAT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 36-20-10 ON TRUE LINE AND HALF WAY BETWEEN THE NORTHWEST CORNER AND THE NORTHEAST CORNER OF SECTION 36-20-10.
 - 1) 65.0' ENE TO A SPIKE & WASHER IN A POWER POLE
 - 2) 19.9' NORTH TO A LINE OF POWER POLES EAST-WEST
 - 3) 20.5' WEST TO THE CENTER OF A CROSS CULVERT
 - 4) 3.0' SOUTH TO THE TRAVELED WAY OF THE ROAD

- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 20, 1985, FOR PROJECT NUMBER 85014, SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF THE NORTH 30 ACRES OF THE SOUTHWEST QUARTER OF SECTION 25-20-10 RECORDED IN VOLUME 413 ON PAGE 675 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 20, 1985, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 25-20-10 FROM HIS 1984 TIES OF RECORD.
 - 1) 65.0' ENE TO A SPIKE & WASHER IN A POWER POLE
 - 2) 19.9' NORTH TO A POWER POLE LINE EAST-WEST
 - 3) 20.5' WEST TO THE CENTER LINE OF A CULVERT NORTH-SOUTH
 - 4) 3.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,645.86' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-20-10, ATTRIBUTABLE TO L. M. GOULD FROM PERMANENT SURVEY BOOK 1 ON PAGE 140
 - 2) 2,645.77' EAST TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-20-10, ATTRIBUTABLE TO L. M. GOULD AND CONFIRMED BY HIM IN 1983
 - 3) 2,148.35' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NORTH 30 ACRES OF THE SW1/4 OF SEC. 25-20-10
 - 4) 2,5641.53' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 25-20-10

CONTINUED ON PAGE 2

- 5) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F25002 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR THE SURVEY OF A 7.9 ACRE TRACT LOCATED IN THE SOUTHWEST QUARTER OF SECTION 25-20-10 FOR PROJECT NUMBER 86071 DATED JULY 30, 1986, AND RECORDED IN VOLUME 427 ON PAGE 31 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 20, 1986, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 25. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,600.86' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH-EAST CORNER OF THE 7.9 ACRE TRACT
 - 2) 2,645.86' WEST TO THE 1/2" REBAR THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-20-10, ATTRIBUTABLE TO L. M. GOULD AND CONFIRMED BY HIM

NORTH QUARTER CORNER 36-20-10