

**SOUTH 1/4 CORNER SECTION 36, TOWNSHIP 20 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 15 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE ROCK 25" X 12" X 2"** ON LEVEL GROUND FOR THE SOUTH 1/4 CORNER OF SECTION 36-20-10 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON NOVEMBER 17, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 27" X 9" X 2" LIMESTONE THEY SET ON A SLOPE TO THE WEST FOR THE CORNER TO SECTIONS 35 & 36-20-10
  - 2) 40.00 CHAINS EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 35" X 10" X 2-1/2" LIMESTONE THEY SET ON A SLOPE TO THE EAST FOR THE CORNER TO TOWNSHIP 20 SOUTH, RANGES 10 & 11 EAST
- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 1 ON PAGE 140 ORDERED BY HINES TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 26-20-10 THAT BEGAN AT 9:00 A.M. ON JULY 26, 1946 AND CONTINUED UNTIL COMPLETED AT 3:00 P.M. ON AUGUST 11, 1946, SAID THAT HE DUG FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 36-20-10. **HE FOUND THE STONE IN PLACE** AT THE SOUTH 1/4 CORNER OF SECTION 36-20-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THIS PERMANENT SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640.33' WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 35-20-10
  - 2) 7,921.0' WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 35-20-10
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-10 SHOWS A **"MONUMENT"** AT THE "S1/4 CORNER SECTION 36-20-10" ON THE 4<sup>TH</sup> STANDARD PARALLEL, BUT DOES NOT DESCRIBE THE MONUMENT.
    - 1) 66.7' SE OF THE SOUTHEAST CORNER OF THE BOTTOM OF A COW STEP
    - 2) 62' SE OF THE SECOND CORNER [OF A COW STEP] EAST OF A DOOR
    - 3) 59.6' SE OF THE SOUTHEAST CORNER OF A FLAGSTONE WALK
  - 4) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 46 AT THE TOP OF THE PAGE SHOWS A **CORNERSTONE** AT THE "S1/4 CORNER SECTION 36-20-10" ON THE 4<sup>TH</sup> STANDARD PARALLEL.
    - 1) 62.0' NNW TO THE 2<sup>ND</sup> CORNER OF THE CHURCH EAST OF THE DOORWAY
    - 2) 66.7' NW TO THE SOUTHEAST CORNER OF THE BOTTOM STEP OF THE CHURCH
    - 3) 59.6' NE TO THE SOUTHEAST CORNER OF THE FLAGSTONE WALK OF THE CHURCH
  - 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 8, 1984, SAID THAT **HE FOUND THE STONE WITH A 1/2" REBAR ON THE EAST SIDE AND BENT OVER THE TOP OF THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 36-20-10 ON THE 4<sup>TH</sup> STANDARD PARALLEL THAT WAS FOUND BY LESLIE M. GOULD IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 140. HE REMOVED THE BENT REBAR AND **HE SET A 5/8" REBAR ON THE NORTH AND SOUTH SIDES OF THE STONE AT THE CENTER OF THE STONE. HE SET A 60 D SPIKE OVER THE TOP OF THE STONE.**
    - 1) 35.8' NORTH TO THE CENTER OF A CORNER FENCE POST SET IN CONCRETE AND A LINE OF FENCE TO THE EAST
    - 2) 66.7' NW TO THE SOUTHEAST CORNER OF CONCRETE STEPS

HIS TIES ARE CONTINUED ON PAGE 2

- 3) 50.7' SOUTH TO A LINE OF FENCE EAST-WEST
  - 4) IN THE CENTERLINE OF F.A.S. ROUTE 412
  - 5) IN LINE WITH A HEDGE ROW TO THE NORTH EXTENDED
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 1991, FOR JOB NUMBER 91021, SAID THAT **HE FOUND THE 60 D SPIKE OVER THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 36-20-10 ON THE 4<sup>TH</sup> STANDARD PARALLEL FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED FEBRUARY 1984. [**NOTE:** DEPUTY BROSEMER FOUND THIS STONE IN 1984 AND HE SET A 5/8" REBAR ON THE NORTH AND SOUTH SIDES OF THE STONE AT THE CENTER OF THE STONE. HE SET A 60 D SPIKE OVER THE TOP OF THE STONE AT THAT TIME – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 1) 35.9' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 2) 50.5' SOUTH TO AN EAST-WEST FENCE LINE
  - 3) 82.0' NE TO THE TOP OF A TELEPHONE PEDESTAL
  - 4) 101.2' NW TO THE SOUTHWEST CORNER OF A BUILDING

SOUTH QUARTER CORNER 36-20-10