

NORTH 1/4 CORNER SECTION 01, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 62 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 9" X 7"** FOR THE NORTH 1/4 CORNER OF SECTION 1-20-11 ON THE TOWNSHIP LINE ON DECEMBER 5, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 24" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-20-11
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 30" X 12" X 3" LIMESTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 11 & 12 EAST AT THE NORTHEAST CORNER OF SEC. 1-20-11
- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36004 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 29.75 ACRE TRACT OF LAND IN THE SOUTHWEST 1/4 OF SECTION 36-19-11 DATED NOVEMBER 21& 22, 1974, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-19-11 ON THE TOWNSHIP LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,630' ± NORTH TO THE "MONUMENT" AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 36-19-11 – NOT DESCRIBED
- 2) 404' WEST ON THE TOWNSHIP LINE TO THE SOUTHWEST CORNER OF THE 29.75 ACRE TRACT, AS WITNESSED BY THE IRON PIN HE SET AT 54' NORTH ON THE RIGHT-OF-WAY LINE

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-11 FOR JAYLENE ARNETT, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 36-19-11 ON THE TOWNSHIP LINE WAS **LOST. HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 36-19-11 ON THE TOWNSHIP LINE AT HALFWAY BETWEEN THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 36-19-11.

- 1) 45.45' SSE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 2) 50.70' SW TO THE SOUTHEAST CORNER OF THE SOUTH HUBGUARD OF A REINFORCED CONCRETE BOX CULVERT
- 3) 55.80' NW TO THE NORTHEAST CORNER OF THE NORTH HUBGUARD OF REINFORCED CONCRETE BOX CULVERT
- 4) 65.0' NNE TO A CONCRETE NAIL & WASHER IN A HEDGE CORNER POST
- 5) 14.5' EAST TO A LINE OF HEDGE TO THE NORTH EXTENDED
- 6) 14.5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 7) 6.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,634.06' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36-19-11
- 2) 2,634.06' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-19-11
- 3) 2,629.94' NORTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 36-19-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 3,957.14' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 36-19-11
 - 5) 5,284.34' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 36-19-11
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE SOUTH 1/4 CORNER OF SECTION 36-19-11 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED SEPTEMBER 2005.
- 1) 45.45' SSE TO A CONCRETE NAIL & WASHER IN A CORNER POST
 - 2) 50.70' SW TO THE SOUTHEAST CORNER OF THE SOUTH HUBGUARD OF A REINFORCED CONCRETE BOX CULVERT
 - 3) 55.80' NW TO THE NORTHEAST CORNER OF THE NORTH HUBGUARD OF REINFORCED CONCRETE BOX CULVERT
 - 4) 65.0' NNE TO A CONCRETE NAIL & WASHER IN A HEDGE CORNER POST
 - 5) 14.5' EAST TO A LINE OF HEDGE TO THE NORTH EXTENDED
 - 6) 14.5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
 - 7) 6.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,630.18' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 36-19-11
 - 2) 3,957.27' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 36-19-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REVERENCE REPORT DATED SEPTEMBER 22, 2009 FOR PROJECT NUMBER 09140-02, THE PLAT FOR MARY'S PLACE SUBDIVISION, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE SOUTH 1/4 CORNER OF SECTION 36-19-11 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 45.45' SSE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 50.70' SW TO THE SOUTHEAST CORNER OF THE SOUTH HUBGUARD
 - 3) 55.80' NW TO THE NORTHEAST CORNER OF THE NORTH HUBGUARD
 - 4) 65.0' NNE TO A CONCRETE NAIL & WASHER IN A HEDGE CORNER FENCE POST
 - 5) 14.5' EAST TO A LINE OF HEDGE TO THE NORTH - EXTENDED
 - 6) 14.5' EAST TO A LINE OF HEDGE TO THE SOUTH - EXTENDED
 - 7) 6.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST
- HIS PLAT DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,634.16' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36-19-11
 - 2) 2,629.99' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 36-19-11
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 22, 2009 FOR PROJECT NUMBER 09330-02, SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF THE EAST HALF OF THE NORTHWEST QUARTER OF SECTION 1-20-11 FOR NORMAN GEIGER, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE

NORTH 1/4 CORNER OF SECTION 1-20-11 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 8) 45.45' SSE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 9) 50.70' SW TO THE SOUTHEAST CORNER OF THE SOUTH HUBGUARD
- 10) 55.80' NW TO THE NORTHEAST CORNER OF THE NORTH HUBGUARD
- 11) 65.0' NNE TO A CONCRETE NAIL & WASHER IN A HEDGE CORNER FENCE POST
- 12) 14.5' EAST TO A LINE OF HEDGE TO THE NORTH – EXTENDED
- 13) 14.5' EAST TO A LINE OF HEDGE TO THE SOUTH – EXTENDED
- 14) 6.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.08' WEST ON THE TOWNSHIP LINE TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 1-20-11, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 50.00' SOUTH ON THE SOUTH RIGHT-OF-WAY LINE OF COUNTY ROAD 130
- 2) 2,634.06' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 1-20-11
- 3) 2,634.06' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND IN A MONUMENT WELL AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 1-20-11
- 4) 2,613.26' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 1-20-11
- 5) 5,254.91' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 1-20-11

NORTH QUARTER CORNER SECTION 01-20-11