

WEST 1/4 CORNER SECTION 01, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 388 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 20" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 2-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.25 CHAINS NORTH TO THE 24" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-20-11 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 21" X 11" X 6" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-20-11

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 75, A **PERMANENT SURVEY** AT THE REQUEST OF W. C. LONG RECORDED IN SURVEY BOOK "F" ON PAGE 155 DATED JUNE 16 & 17, 1903, FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF SECTION 12-20-11, AND THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SAID SECTION 12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 1-20-11 ON THIS **PERMANENT SURVEY** AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-20-11 NORTH TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 1-20-11 ON THE TOWNSHIP LINE. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 172 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 162" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 22, 2009 FOR PROJECT NUMBER 09330-02, SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF THE EAST HALF OF THE NORTHWEST QUARTER OF SECTION 1-20-11 FOR NORMAN GEIGER, SAID THAT HE CONSIDERED THAT THE WEST 1/4 CORNER OF SECTION 1-20-11 WAS **LOST** IN EAST-WEST POSITION AND **OBLITERATED** IN NORTH-SOUTH POSITION. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 1-20-11 ON TRUE LINE BETWEEN THE NORTHWEST CORNER OF SECTION 1-20-11 ON THE TOWNSHIP LINE AND THE SOUTHWEST CORNER OF SECTION 1-20-11, AND AT THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER.
 - 1) IN LINE WITH A FENCE TO THE WEST
 - 2) 1.0' NORTH TO A HEDGE TO THE EAST
 - 3) 28.0' WNW TO THE TOP CENTER OF A 5" PIPE POST
 - 4) 45.70' SSE TO A 60 D NAIL & BOTTLE CAP IN THE WEST FACE OF A CUT-OFF POWER POLE
 - 5) 8.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,588.49' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF SECTION 1-20-11 ON THE TOWNSHIP LINE
 - 2) 2,644.97' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF SECTION 1-20-11
 - 3) 1,316.87' EAST TO THE 5/8" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 1-20-11
 - 4) 2,633.74' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 1-20-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 5,267.43' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 1-20-11 ON THE RANGE LINE

WEST QUARTER CORNER 01-20-11