

NORTH 1/16TH CORNER NORTHEAST QUARTER OF SECTION 04, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 20, 2013 FOR PROJECT NUMBER 13191, SURVEY F33002 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 TO SURVEY THE NORTH LINE OF THE SOUTHEAST 1/4 OF SECTION 33-19-11 FOR DOUDICAN, SAID THAT **THE SET A 1/2" X 24" IRON PIN WITH HIS "L.S. 752" CAP** FOR THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 33-19-11 ON THE TOWNSHIP LINE AND HALFWAY BETWEEN THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 33-19-11.
 - 1) 25.8' NW TO A 40 D NAIL & WASHER IN A BRACE POST
 - 2) 21.75' NNE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 3) 33.5' SE TO A CONCRETE NAIL & WASHER IN A FENCE POST
 - 4) 1' WEST TO A LINE OF FENCE TO THE NORTH
 - 5) 3' SOUTH TO THE TRAVELED WAY [OF COUNTY ROAD 130] EAST-WEST
 - 6) **4.1' SSW TO A 1/2" BENT IRON PIN FOUND**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,318.95' WEST ON THE TOWNSHIP LINE TO A 5/8" IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 33-19-11
 - 2) 1,318.95' EAST ON THE TOWNSHIP LINE TO A 5/8" IRON PIN OVER THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 33-19-11
 - 3) 1,326.36' NORTH TO THE 1/2" X 24" IRON PIN WITH HIS "L.S. 752" CAP HE SET FOR THE CENTER CORNER OF THE SE1/4 OF SECTION 33-19-11
 - 4) 2,652.72' NORTH TO THE THEORETICAL POSITION FOR THE NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 33-19-11 – NO MARKER SET AS THE TRUE POSITION FALLS IN A CREEK AREA

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 04-20-11