

WEST 1/4 CORNER SECTION 04, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 399 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 18" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 21" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-20-11 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-11

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 149 DATED MARCH 13, 1883 AT THE REQUEST OF DAVID JONES TO ESTABLISH THE CENTER CORNER OF SECTION 5-20-11 AND THE OUTSIDE 1/8TH CORNERS, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 5-20-11 ON THIS **INFORMAL SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 79.80 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-20-11

- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 TO SURVEY TO ESTABLISH AND SET THE CORNERS OF A 40 ACRE TRACT OF GROUND DESCRIBED AT THE NORTHEAST QUARTER OF THE NORTHEAST QUARTER OF SECTION 5-20-11 AND TO SUBDIVIDE THE SAME INTO FOUR (4) TEN ACRE TRACTS DATED MAY 17, 1973, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 5-20-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 660' WEST TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 2) 1,320' WEST TO THE IRON PIN HE SET FOR THE SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 5
 - 3) 660' NORTH TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 4) 1,320' NORTH TO THE IRON PIN HE SET FOR THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 5
 - 5) 1,981.5' NORTH TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 6) 2,643' NORTH TO THE IRON PIN AT THE NORTHEAST CORNER OF SECTION 5-20-11 ON THE TOWNSHIP LINE

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 9, 2001, FOR PROJECT NUMBER 01073-02, SURVEY F04002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A TRACT OF LAND LOCATED IN THE SOUTHWEST QUARTER AND THE SOUTHEAST QUARTER OF SECTION 4-20-11, SAID THAT **HE FOUND A 1/2" REBAR** OF UNCERTAIN ORIGIN BUT IN A REASONABLE POSITION FOR THE WEST 1/4 CORNER OF SECTION 4-20-11.
 - 1) 26.5' EAST TO A 40 D NAIL & WASHER IN A FENCE POST
 - 2) 21.7' WEST TO A 40 D NAIL & WASHER IN A FENCE POST
 - 3) 42.9' NW TO 40 A D NAIL & WASHER IN A CORNER FENCE POST
 - 4) 6.6' SOUTH TO A LINE OF FENCE TO THE EAST
 - 5) IN LINE WITH A FENCE TO THE WEST
 - 6) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,638.94' NORTH TO THE SQUARE #4 REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-20-11 ON THE TOWNSHIP LINE

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,634.63' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 4-20-11
 - 3) 2,635.73' EAST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 4-20-11
 - 4) 5,275.34' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/4 CORNER OF SECTION 4-20-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 26, 2002, FOR PROJECT NUMBER 02157-02, SURVEY F04003 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR FIVE TRACTS IN THE FRACTIONAL NORTHWEST QUARTER OF SECTION 4-20-11, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE WEST 1/4 CORNER OF SECTION 4-20-11 FROM HIS 2001 TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. THIS SECTION CORNER IS ALSO THE SOUTHWEST CORNER OF TRACT 1.
- 1) 26.5' EAST TO A 40 D NAIL & WASHER IN A FENCE POST
 - 2) 21.7' WEST TO A 40 D NAIL & WASHER IN A FENCE POST
 - 3) 42.9' NW TO 40 A D NAIL & WASHER IN A CORNER FENCE POST
 - 4) 6.6' SOUTH TO A LINE OF FENCE TO THE EAST
 - 5) IN LINE WITH A FENCE TO THE WEST
 - 6) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 493.50' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE P.O.B. OF TRACT 2, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20' EAST ON THE EAST RIGHT-OF-WAY LINE OF COUNTY ROAD "J"
 - 2) 887.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF TRACT 2, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20' EAST ON THE SOUTH RIGHT-OF-WAY LINE OF COUNTY ROAD "J"
 - 3) 2,638.94' NORTH TO THE SQUARE #4 REBAR HE FOUND AT THE NORTHWEST CORNER OF THE W/12 OF THE NW1/4 OF SECTION 4-20-11, AND THE NORTHWEST CORNER OF TRACT 3
 - 4) 2,634.63' SOUTH TO THE 1/2' REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-20-11
 - 5) 1,317.86' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 4-20-11, AND THE SOUTHEAST CORNER OF TRACT 1
 - 6) 2,635.73' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 4-20-11
 - 7) 5,275.34' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/4 CORNER OF SECTION 4-20-11

WEST QUARTER CORNER 04-20-11