

NORTH 1/4 CORNER SECTION 05, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 60 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 11" X 4"** FOR THE NORTH 1/4 CORNER OF SECTION 5-20-11 ON THE TOWNSHIP LINE ON DECEMBER 5, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 23" X 8" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-20-11
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 21" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-20-11

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 149 DATED MARCH 13, 1883 AT THE REQUEST OF DAVID JONES TO ESTABLISH THE CENTER CORNER OF SECTION 5-20-11 AND THE OUTSIDE 1/8TH CORNERS, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-20-11 ON THE TOWNSHIP LINE ON THIS **INFORMAL SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 79.53 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-20-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 DATED MARCH 25-31, 1902 ORDERED BY CHARLES EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4, THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE EAST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 3-20-11, AND WILL RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 5-20-11 AS HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-20-11 EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-10-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 69, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 122 DATED DECEMBER 21, 2006 BY ORDER OF THE BOARD OF COUNTY COMMISSIONERS TO MARK THE RIGHT-OF-WAY OF THE COUNTY ROAD IN THE NORTHEAST CORNER OF SECTION 6-20-11 DOES NOT MENTION THE NORTH 1/4 CORNER OF SECTION 5-21-11 WHEN HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 3-20-11 WEST TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-20-11. SEE PACKET "M 89" IN MISCELLANEOUS DRAWER 4 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.

- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F32001 IN THE SURVEY FILE FOR SECTIONS 17-36, TOWNSHIP 19-11 SHOWING THE SUBDIVISION OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 32-19-11 INTO THREE EQUAL TRACTS, BUT NOT DATED, IT SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32-19-11 ON THE TOWNSHIP LINE. THERE IS NO DESCRIPTION OF THE

MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. IT APPEARS FROM HIS DRAWING THAT A HEDGE ROW BEARS NORTH. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' NORTH TO THE CORNER POST AT THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 32-19-11
 - 2) 439.333' WEST ON THE TOWNSHIP LINE TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 3) 878.666' WEST ON THE TOWNSHIP LINE TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 4) 1,318' WEST ON THE TOWNSHIP LINE TO THE IRON PIN HE SET FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 32-19-11
- 6) BRINK & DUNWOODY ENGINEERS PLANS FOR PROJECT NUMBER 56-S-1143 (2) SAID THAT THERE WAS A **1/2" SQUARE IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 5-19-11 ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS 1/2" SQUARE IRON PIN MAY HAVE BEEN "HEELED-IN" FOR THE PLANS FOR THIS PROJECT!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 19.7' NORTH TO A CORNER FENCE POST
 - 2) 29.25' NW TO THE BASE OF A POST
 - 3) EAST END HEDGE
 - 4) WEST SIDE DRIVE

NORTH QUARTER CORNER SECTION 05-20-11