

NORTH 1/16TH CORNER NORTHEAST QUARTER OF SECTION 05, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 TO SURVEY TO ESTABLISH AND SET THE CORNERS OF A 40 ACRE TRACT OF GROUND DESCRIBED AT THE NORTHEAST QUARTER OF THE NORTHEAST QUARTER OF SECTION 5-20-11 DATED MAY 17, 1973, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 5-20-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 660' EAST ON THE TOWNSHIP LINE TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 2) 1,320' EAST ON THE TOWNSHIP LINE TO THE IRON PIN AT THE NORTHEAST CORNER OF SECTION 5-20-11
 - 3) 661.50' SOUTH TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 4) 1,323' SOUTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF THE NE1/4 OF SECTION 5-20-11
 - 5) 1,983' SOUTH TO THE IRON PIN HE SET FOR A TRACT CORNER
 - 6) 2,643' SOUTH TO THE IRON PIN HE SET FOR THE SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 3-20-11
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F05003 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE WEST LINE OF THE SOUTHWEST QUARTER OF THE NORTHEAST QUARTER OF THE NORTHEAST QUARTER OF SECTION 5-20-11 FOR PROJECT NUMBER 02088-02 DATED MARCH 23, 2002 SHOWS THAT **HE FOUND A 1/2" REBAR PAINTED ORANGE ON TOP ATTRIBUTABLE TO LESLIE M. GOULD SURVEYS DATED MAY AND JULY 1974** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 5-20-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.60' EAST ON THE TOWNSHIP LINE TO THE 1/2" IRON BAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 NE1/4 OF SECTION 5-20-11
- 2) 659.48' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NE1/4 OF THE NE1/4 OF SECTION 5-20-11 – TRUE POSITION FALLS IN A CREEK
- 3) 689.12' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752 CAP HE SET
- 4) 855.80' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 5) 950.57' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 6) 1,091.09' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 7) 1,161.38' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 8) 1,318.96' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 NE1/4 OF SECTION 5-20-11

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 05-20-11