

NORTHWEST CORNER SECTION 05, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 60 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 8" X 3"** FOR THE CORNER TO SECTIONS 5 & 6-19-11 ON THE TOWNSHIP LINE ON DECEMBER 5, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 18" X 11" X 4" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 5-20-11
 - 2) 80.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 21" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-20-11
 - 3) 39.90 CHAINS SOUTH TO THE 20" X 18" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-20-11
 - 4) 79.90 CHAINS SOUTH TO THE 28" X 10" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-20-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 83 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 338 TO 340 PETITIONED BY J. SONNEDECKER AND OTHERS FOR THREE COUNTY ROADS IN TOWNSHIPS 19-11 AND 20-11 [PACKET 228 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 1, 1880, WERE ESTABLISHED AS 40 FOOT WIDE ROADS ON OCTOBER 5, 1880 AS NOTED BY I. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON NOVEMBER 5, 1880 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 6-20-11 ON THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE SECOND ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 31-19-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
- 2) THE SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 2 MILES TO THE SOUTHEAST CORNER OF SECTION 7-20-11 TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 191 DATED OCTOBER 1, 1880, FOR THREE COUNTY ROADS IN TOWNSHIPS 19-11 & 20-11, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE ON THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE SECOND ROAD EXTENDS NORTH ON THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-19-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
- 2) THE SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-20-11 TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 178 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 298 TO 300 PETITION BY EDWARD DAVIS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-10 & 20-11 [PACKET 426 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1882, WAS ESTABLISHED AS A 40 FOOT ROAD ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT

HE SET A STONE MARKED "II M" AT OR NEAR THE NORTHWEST CORNER OF SECTION 5-20-11 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE HE MARKED "I M" AT THE TOWNSHIP CORNER OF RANGES 10 & 11; THEN CONTINUES WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "III M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 4-20-11; THEN CONTINUES EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "IIII M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 3-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 15 FOR A ROAD IN TOWNSHIP 20, RANGES 10 & 11, DATED JUNE 13, 1882, SAID THAT **HE SET A ROAD STONE MARKED "II M"** AT THE NORTHEAST CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE HE MARKED "I M" AT THE TOWNSHIP CORNER OF RANGES 10 & 11; THEN CONTINUES WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "III M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 4-20-11; THEN CONTINUES EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "IIII M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 3-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 149 DATED MARCH 13, 1883 AT THE REQUEST OF DAVID JONES TO ESTABLISH THE CENTER CORNER OF SECTION 5-20-11 AND THE OUTSIDE 1/8TH CORNERS, SAID THAT **HE SET A STONE** FOR THE NORTHWEST CORNER OF SECTION 5-20-11 ON THE TOWNSHIP LINE BY EXTENDING A LINE NORTH FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-20-11 THROUGH THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SAID SECTION 5-20-11 WITH THE INTERSECTION OF THE TOWNSHIP LINE ON THIS INFORMAL SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.45 CHAINS SOUTH TO THE STONE HE SET FOR THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 5-20-11
- 2) 39.45 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-20-11
- 3) 79.45 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-20-11

- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT **HE FOUND A SMALL STONE 4" X 4" X 12"** **"SOME THOUGHT TO BE THE NORTHEAST CORNER OF SECTION 6-20-11"** ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HE DID NOT SAY IS HE ACCEPTED THIS STONE AS HE RAN THE TOWNSHIP LINE FROM

THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-20-11 WEST TO THE STONE THAT HE FOUND IN THE GROUND IN GOOD CONDITION AT THE NORTH 1/4 CORNER OF SECTION 5-20-10. HE FOUND THE TOTAL DISTANCE BETWEEN THESE TWO STONES TO BE 36,867 FEET.

- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 DATED MARCH 25-31, 1902 ORDERED BY CHARLES EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4, THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE EAST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 3-20-11, AND WILL RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 5-20-11 AS HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-20-11 EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 69, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 122 DATED DECEMBER 21, 2006 BY ORDER OF THE BOARD OF COUNTY COMMISSIONERS TO MARK THE RIGHT-OF-WAY OF THE COUNTY ROAD IN THE NORTHEAST CORNER OF SECTION 6-20-11 SAID THAT HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 3-20-11 TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-20-11. HE NOTED THAT HE "CORRECTED THE **STAKE AT THE NORTHEAST CORNER OF SECTION 6-20-11** 6 LINKS SOUTH TO A POINT 3 FEET NORTH OF THE CENTER OF THE ROAD, WHICH IS 40 FEET WIDE AT THIS PLACE AS NOW FENCED". SEE PACKET "M 89" IN MISCELLANEOUS DRAWER 4 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.
- 9) BRINK & DUNWOODY ENGINEERS PLANS FOR PROJECT NO. 56-S-1143 (2) SAID THAT THERE WAS A **1/2" SQUARE IRON PIN AT THE "INTERSECTION"**. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS MAY HAVE BEEN "HEELED-IN" FOR THIS PROJECT - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) P. I. STATION 153+07.1
 - 2) 60.85' SW TO A SPIKE IN A TELEPHONE POLE
 - 3) 68.8' SE TO A SPIKE IN A TELEPHONE POLE

NORTHWEST CORNER SECTION 05-20-11