

**WEST 1/4 CORNER SECTION 05, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 405 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 18" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-20-11 ON JULY 3, 1857.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.90 CHAINS NORTH TO THE 23" X 8" X 3" LIMESTONE HE SET FOR THE CORNER TO SECTIONS 5 & 6-20-11 ON THE TOWNSHIP LINE
  - 2) 40.00 CHAINS SOUTH TO THE 28" X 10" X 2" LIMESTONE HEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-20-11
  
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 149 DATED MARCH 13, 1883 AT THE REQUEST OF DAVID JONES TO ESTABLISH THE CENTER CORNER OF SECTION 5-20-11 AND THE OUTSIDE 1/8<sup>TH</sup> CORNERS, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 5-20-11 ON THIS **INFORMAL SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.70 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-20-11
  - 2) 20.00 CHAINS NORTH TO THE STONE HE SET FOR THE WEST 1/8<sup>TH</sup> CORNER THE NW1/4 OF SECTION 5-20-11
  - 3) 39.45 CHAINS NORTH TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 5-20-11 ON THE TOWNSHIP LINE
  - 4) 79.80 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 5-20-11
  
- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT SET A **TEMPORARY POINT** FOR THE EAST 1/4 CORNER OF SECTION 6-20-11 ON THIS **PERMANENT SURVEY**. HE USED THIS TEMPORARY POINT TO SET A 24" X 4" X 9" LIMESTONE MARKED "+" ON THE TOP AND ON THE WEST SIDE FOR THE PERMANENT CENTER CORNER OF SECTION 6-20-11.
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MAY 12, 2004, FOR PROJECT NUMBER 04071-02, SURVEY F05002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EG, SAID THAT **HE FOUND A 1/2" REBAR**, AND **HE ACCEPTED THIS REBAR AS THE WEST 1/4 CORNER OF SECTION 5-20-11**.
  - 1) 36.35' SE TO A CONCRETE NAIL & WASHER IN A GATE POST
  - 2) 33.5' WEST TO A CONCRETE NAIL & WASHER IN A RAILROAD TIE CORNER POST
  - 3) 37.8' NE TO A CONCRETE NAIL & WASHER IN A 6" MULBERRY TREE
  - 4) IN LINE WITH A FENCE AND A HEDGE TO THE EAST
  - 5) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL ROAD "H" NORTH-SOUTH
  - 6) NORTHING = 49,460.2570 EASTING = 4,978.1620HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,235.62' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
  - 2) 2,595.62' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A WITNESS CORNER
  - 3) 2,635.62' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5-20-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 5,263.53' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 8-20-11

WEST QUARTER CORNER 05-20-11