

NORTH 1/4 CORNER SECTION 06, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 60 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 11" X 3"** FOR THE NORTH /4 CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE ON DECEMBER 5, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.70 CHAINS WEST ON THE TOWNSHIP LINE TO THE 24" X 14" X 2-1/2" SANDSTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-20-11
- 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 23" X 8" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-20-11
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT **HE SET A 26" X 6" X 4" LIMESTONE MARKED "1/4" ON THE NORTH SIDE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-20-11 WEST TO THE STONE THAT HE FOUND IN THE GROUND IN GOOD CONDITION AT THE NORTH 1/4 CORNER OF SECTION 5-20-10. HE FOUND THE TOTAL DISTANCE BETWEEN THESE TWO STONES TO BE 36,867 FEET. HE USED THIS STONE TO SET A 24" X 4" X 9" LIMESTONE MARKED "+" ON THE TOP AND ON THE WEST SIDE FOR THE PERMANENT CENTER CORNER OF SECTION 6-20-11.

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 DATED MARCH 25-31, 1902 ORDERED BY CHARLES EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4, THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE EAST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 3-20-11, AND WILL RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE, WHICH STANDS 20 FEET NORTH OF A FENCE EXTENDING SOUTH**. HE RAN THE TOWNSHIP LINE FROM THIS STONE EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 200.20 CHAINS EAST ON THE TOWNSHIP LINE TO THE STAKE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 3-20-11
- 2) 240.38 CHAINS EAST ON THE TOWNSHIP LINE TO THE STAKE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 3-20-11
- 3) 260.47 CHAINS EAST ON THE TOWNSHIP LINE TO THE 17" X 17" X 3" STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SEC. 3-20-11
- 4) 280.56 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 3-20-11, THAT WAS SET BY HIBBEN IN 1881
- 5) 360.36 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-11

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 158, A ROAD SURVEY ORDERED BY THE BOARD OF COUNTY COMMISSIONERS RECORDED IN SURVEY BOOK "F" ON PAGE 122 DATED DECEMBER 21, 1906, SAID THAT **HE FOUND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE, WHICH STANDS 20 FEET NORTH OF A FENCE EXTENDING SOUTH.** HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THIS CORNER TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 3-20-11 ON THIS ROAD SURVEY. SEE PACKET "M 89" IN MISCELLANEOUS DRAWER 4 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-11 SHOWS A **STONE** AT THE "N1/4 CORNER SECTION 6-20-11" ON THE TOWNSHIP LINE.
 - 1) 20' NORTH TO A CORNER FENCE POST
 - 2) 40' NE TO A PINE STAKE IN A FENCE LINE
 - 3) 40' SE TO A PINE STAKE IN A FENCE LINE
- 6) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 63 AT THE TOP OF THE PAGE SHOWS A **STONE** AT THE "N1/4 CORNER SECTION 6-20-11" ON THE TOWNSHIP LINE.
 - 1) 20' NORTH TO THE NEAR FACE OF A CORNER FENCE POST
 - 2) 40' NE TO A PINE STAKE IN THE EAST-WEST FENCE LINE
 - 3) 40' SE TO A PINE STAKE IN THE EAST-WEST FENCE LINE
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 22, 2007 FOR PROJECT NUMBER 07230-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF TWO TRACTS IN THE WEST HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR NELLIE OWENS, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 6-20-11 ON THE TOWNSHIP LINE THAT WAS SET BY MATTHEW BROWN IN 1888 IN SURVEY BOOK "F" ON PAGE 132. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE CENTER OF THE STONE.**
 - 1) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST
 - 2) 2.0' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
 - 3) IN LINE WITH A FENCE TO THE NORTH EXTENDED
 - 4) 24.60' SSW TO THE EAST GATE POST [CONCRETE NAIL & WASHER]
 - 5) 35.85' SW TO A CONCRETE NAIL & WASHER IN THE WEST GATE POST
 - 6) 27.0' NW TO A 40 D NAIL & WASHER IN A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,320.04' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 6-20-11, THAT WAS SET BY MATTHEW BROWN
 - 2) 2,614.30' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 36-19-10
 - 3) 5,248.36' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-19-10
 - 4) 7,882.42' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-19-10

NORTH QUARTER CORNER SECTION 06-20-11