

NORTHWEST CORNER SECTION 06, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 40 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 14" X 2-1/2" WITH A MOUND OF ROCKS** FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-20-11 ON NOVEMBER 25, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.70 CHAINS EAST ON THE TOWNSHIP LINE TO THE 21" X 11" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-20-11
- 2) 79.70 CHAINS EAST ON THE TOWNSHIP LINE TO THE 23" X 8" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-20-11
- 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 21" X 16" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 1-20-11
- 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 28" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-20-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 178 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 298 TO 300 PETITION BY EDWARD DAVIS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-10 & 20-11 [PACKET 426 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1882, WAS ESTABLISHED AS A 40 FOOT ROAD ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT THE TOWNSHIP CORNER STONE WAS DOWN, SO **HE SET A STONE MARKED "I M"** AT THE NORTHEAST CORNER OF SECTION 1-20-10 AT THE TOWNSHIP CORNER BETWEEN RANGES 10 AND 11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "II M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 5-20-11; THEN CONTINUES EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "III M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 4-20-11; THEN CONTINUES EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "IIII M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 3-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 15 FOR A ROAD IN TOWNSHIP 20, RANGES 10 & 11, DATED JUNE 13, 1882, SAID THAT **HE SET A ROAD STONE MARKED "I M"** FOR THE NORTHEAST CORNER OF SECTION 1-20-10 AT THE TOWNSHIP CORNER ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "II M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 5-20-11; THEN CONTINUES EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED " III M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 4-20-11; THEN CONTINUES EAST ON THE TOWNSHIP LINE FOR 1 MILE TO THE ROAD STONE MARKED "IIII M" HE SET AT OR NEAR THE

NORTHWEST CORNER OF SECTION 3-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 275 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 50 TO 52 PETITIONED BY T. H. WILLIAMS AND OTHERS FOR THE VACATION AND RELOCATION OF COUNTY ROADS IN TOWNSHIPS 19-10, 19-11, 20-10 AND 20-11 [PACKET 522 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 17, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 10, 1884, AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 9, 1884 BY ROLAND LAKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-20-10 AT THE TOWNSHIP CORNER ON THE ROAD APPROVED BY THE VIEWERS ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR AN UNCALLED DISTANCE TO AN ANGLE STONE HE SET FOR A SERIES OF ANGLES; THEN INTERSECTS THE SECTION LINE AT A ROAD STONE HE SET AT 235 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 36-19-10; THEN CONTINUES NORTH ON THE SECTION LINES FOR 235 FEET TO THE NORTHEAST CORNER OF SECTION 36-19-10 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-20-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT HE WAS NOT ABLE TO FIND ANY PART OF THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-20-11 ON THIS **PERMANENT SURVEY**. HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-20-11 WEST TO THE STONE THAT HE FOUND IN THE GROUND IN GOOD CONDITION AT THE NORTH 1/4 CORNER OF SECTION 5-20-10. HE FOUND THE TOTAL DISTANCE BETWEEN THESE TWO STONES TO BE 36,867 FEET.
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 22, 2007 FOR PROJECT NUMBER 07230-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF TWO TRACTS IN THE WEST HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR NELLIE OWENS, SAID THAT HE DEEMED THAT THE SOUTHEAST CORNER OF SECTION 36-19-10 AT THE TOWNSHIP CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTHEAST CORNER OF SECTION 36-19-10 AT THE TOWNSHIP CORNER ON LINE FROM THE EAST FROM A PRIOR MATTHEW BROWN SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 132. **[NOTE: THIS SHOULD BE SURVEY BOOK "F", NOT SURVEY BOOK "B" – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 6.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST
 - 2) 7.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G" NORTH-SOUTH
 - 3) 40.25' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 4) 36.75' SW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 18.30' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST

HIS TIES ARE CONTINUED ON PAGE 3

- 6) 32.75' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,650.50' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-19-10
 - 2) 5,267.96' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-10
 - 3) 1,294.26' EAST ON THE TOWNSHIP LINE TO MATTHEW BROWNS STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 6-20-11
 - 4) 2,614.30' EAST ON THE TOWNSHIP LINE TO MATTHEW BROWNS STONE HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF SEC. 6-20-11
 - 5) 2,634.06' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-19-10
 - 6) 5,268.12' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-19-10

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 25, 2009 FOR PROJECT NUMBER 09247-02, SURVEY F12001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF THE SOUTH HALF OF SECTION 12-20-10 FOR DONNA WILLIAMS, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 1-20-10 AT THE TOWNSHIP CORNER FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 2007.
 - 1) 6.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST
 - 2) 7.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G" NORTH-SOUTH
 - 3) 40.25' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 4) 36.75' SW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 18.30' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 6) 32.75' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 5,276.51' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 12-20-10
 - 2) 7,914.77' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-20-10
 - 3) 10,549.05' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-20-10

NORTHWEST CORNER 06-20-11