

**WEST 1/4 CORNER SECTION 06, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 40 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 16" X 3"** FOR THE WEST 1/4 CORNER OF SECTION 6-20-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 25, 1856.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 14" X 2-1/2" SANDSTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-20-11
  - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 28" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-20-11
  
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT HE SET A **TEMPORARY POINT** FOR THE WEST 1/4 CORNER OF SECTION 6-20-11 ON THE RANGE LINE. HE USED THIS TEMPORARY POINT TO SET A 24" X 4" X 9" LIMESTONE MARKED "+" ON THE TOP AND ON THE WEST SIDE FOR THE PERMANENT CENTER CORNER OF SECTION 6-20-11.

WEST QUARTER CORNER 06-20-11