

NORTHWEST CORNER SECTION 07, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 40 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 12" X 4"** FOR THE CORNER TO SECTIONS 6 & 7-20-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 35, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.85 CHAINS EAST TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-20-11
 - 2) 79.85 CHAINS EAST TO THE 28" X 10" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-20-11
 - 3) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 21" X 16" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-20-11
 - 4) 80.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 14" X 2-1/2" SANDSTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-20-11
 - 5) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 23" X 8" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 7-20-11
 - 6) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-20-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 191 DATED OCTOBER 1, 1880, FOR THREE COUNTY ROADS IN TOWNSHIPS 19-11 & 20-11, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 7-20-11 ON THE RANGE LINE AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-20-11 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY WITH TWO ANGLE POINTS ON THE NORTH LINE OF SECTION 8-20-11
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 83 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 338 TO 340 PETITIONED BY J. SONNEDECKER AND OTHERS FOR THREE COUNTY ROADS IN TOWNSHIPS 19-11 AND 20-11 [PACKET 228 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 1, 1880, WERE ESTABLISHED AS 40 FOOT WIDE ROADS ON OCTOBER 5, 1880 AS NOTED BY I. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON NOVEMBER 5, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 7-20-11 ON THE RANGE LINE FOR THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD EXTENDS EAST ON THE SECTION LINES TO THE TO THE NORTHWEST CORNER OF SECTION 8-20-11; THEN FIRST ANGLES SOUTHEASTERLY THEN INTERSECTS THE SECTION LINE AT 1,965 FEET WEST OF THE NORTH 1/4 CORNER OF SECTION 8-20-11; THEN CONTINUES ON THE SECTION LINE TO A POINT 1,335 FEET EAST OF THE NORTH 1/4 CORNER OF SECTION 8 TO AN ANGLE TO THE SOUTHEASTERLY AND INTERSECTS THE SECTION LINE AT A POINT 910 FEET WEST OF THE NORTHEAST CORNER OF SECTION 8-20-11 AND CONTINUES EAST ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 9-20-11 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 84 DATED DECEMBER 21, 1883 FOR A ROAD IN TOWNSHIP 20, RANGE 10 FOR ADAM STOTTER, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 1-20-10 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD SURVEY EXTENDED WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-20-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) HE NOTED ON HIS DRAWING THAT THE ROAD FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-20-10 TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-20-10 ON THE RANGE LINE WAS **DISALLOWED**
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 244 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 562 TO 564 PETITIONED BY ADAM STOTTER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-10 [PACKET 490 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON DECEMBER 21, 1883, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FROM THE PLACE OF BEGINNING TO THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 10-20-10 ON JANUARY 19, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 29, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 12-20-10 ON THE RANGE LINE TO COMMENCE THE ROAD ALLOWED ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2-3/4 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 10-20-10 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 275 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 50 TO 52 PETITIONED BY T. H. WILLIAMS AND OTHERS FOR THE VACATION AND RELOCATION OF COUNTY ROADS IN TOWNSHIPS 19-10, 19-11, 20-10 AND 20-11 [PACKET 522 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 17, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 10, 1884, AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 9, 1884 BY ROLAND LAKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 12-20-10 ON THE ROAD APPROVED BY THE VIEWERS ON THIS SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 1 MILE TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHEAST CORNER OF SECTION 1-20-10; THEN CONTINUES NORTH ON THE RANGE LINE FOR AN UNCALLED DISTANCE TO AN ANGLE STONE HE SET FOR A SERIES OF ANGLES; THEN INTERSECTS THE SECTION LINE AT A ROAD STONE HE SET AT 235 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 36-19-10; THEN CONTINUES NORTH ON THE SECTION LINES FOR 235 FEET TO THE NORTHEAST CORNER OF SECTION 36-19-10 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-20-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT HE SET A **TEMPORARY POINT** FOR THE SOUTHWEST CORNER OF SECTION 6-20-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
- 7) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 101
ON MARCH 13, 1956 A PETITION SIGNED BY RAY M. BEYER AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 20-11 WAS PRESENTED TO VESPER M. SHEELEY, JR., COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND W. D. KRETSINGER, COUNTY ENGINEER, ON APRIL 5, 1956 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON APRIL 5, 1956 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING AT A POINT 1,000 FEET MORE OR LESS WEST OF THE NORTHEAST CORNER OF SECTION 7-20-11 AND TERMINATING AT THE NORTHWEST CORNER OF SAID SECTION 7-20-11.
- 8) COMMISSIONER'S ROAD JOURNAL BOOK "C", PAGE 11
ON DECEMBER 3, 2001, A PETITION SIGNED BY DONNA A. WILLIAMS AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 20-10 WAS PRESENTED TO LANNETTE LINEBARGER, DEPUTY COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON FEBRUARY 14, 2002 AND THE FINAL ORDER DATED FEBRUARY 14, 2002 ORDERED THAT THE FOLLOWING ROAD BE **VACATED**:
- 1) BEGINNING ON THE EASTERLY RIGHT-OF-WAY LINE OF ROAD "F", BEING 25 FEET EAST OF THE NORTHWEST CORNER OF SECTION 12-20-10; THENCE EASTERLY ALONG THE CENTERLINE OF SAID ROAD 120, BEING THE SECTION LINE BETWEEN SECTIONS 1 AND 12 TO THE WESTERLY RIGHT-OF-WAY LINE OF ROAD "G", BEING 20 FEET WEST OF THE NORTHEAST CORNER OF SAID SECTION 12-20-10, AND THERE ENDING.
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 25, 2009 FOR PROJECT NUMBER 09247-02, SURVEY F12001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF THE SOUTH HALF OF SECTION 12-20-10 FOR DONNA WILLIAMS, SAID THAT HE DEEMED THAT THE NORTHEAST CORNER OF SECTION 12-20-10 ON THE RANGE LINE WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHEAST CORNER OF SECTION 12-20-10 ON THE RANGE LINE AT ONE THIRD OF THE DISTANCE BETWEEN THE NORTHEAST CORNER OF SECTION 1-20-10 AND THE EAST 1/4 CORNER OF SECTION 12-20-10.
- 1) 19.05' WNW TO THE TOP CENTERLINE OF A 6" PIPE CORNER FENCE POST
 - 2) 7.0' NORTH TO A LINE OF FENCE TO THE WEST
 - 3) 24.55' ENE TO A CONCRETE NAIL & BOTTLECAP IN THE WEST FACE OF A CORNER FENCE POST
 - 4) 31.7' SE TO A CONCRETE NAIL & BOTTLECAP IN THE WEST FACE OF A GATE POST
 - 5) 6.5' EAST TO THE TRAVELED WAY OF COUNTY ROAD "G" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,276.51' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-20-10
 - 2) 2,638.26' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-20-10
 - 3) 5,272.54' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-20-10

HIS INFORMATION IS CONTINUED ON PAGE 4

- 4) 2,642.64' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 12-20-10
- 5) 5,285.28' WEST TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 12-20-10

NORTHWEST CORNER 07-20-11