

CENTER CORNER SECTION 08, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 58 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 155 DATED FEBRUARY 15, 1872 TO ESTABLISH THE CORNERS TO THE SOUTH 1/4 OF THE NORTHEAST 1/4 OF SECTION 8-20-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 8-20-11 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,316-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 8-20-11
 - 2) 2,633' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-20-11
- 2) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE DATED SEPTEMBER 18, 2002, FOR PROJECT NUMBER 01406-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE SOUTHEAST QUARTER AND THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 8-20-11, SAID THAT SHE DEEMED THAT THE CENTER CORNER OF SECTION 8-20-11 WAS **LOST** IN EAST-WEST POSITION, AND SHE RESET IT BY THE PHYSICAL EVIDENCE. SHE DEEMED THAT THIS CORNER WAS **OBLITERATED** IN NORTH-SOUTH POSITION, AND SHE RESET IT IN ON LINE WITH THE SOUTH 1/4 AND NORTH 1/4 CORNERS. **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 8-20-11.
- 1) 0.20' EAST TO A LINE OF FENCE NORTH-SOUTH
 - 2) 5.45' SOUTH TO A CONCRETE NAIL & BOTTLE CAP IN THE NORTH GATE POST
 - 3) 5.85' SOUTH TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
 - 4) IN LINE WITH HEDGE TO THE EAST, EXTENDED WEST

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,314.00' NORTH TO THE CORNER FENCE POST SHE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 8-20-11, AS REFERENCED BY TWO 1/2" REBARS WITH HER "LS 1130" CAPS SHE SET AS WITNESSES
- 2) 2,628.00' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 8-20-11
- 3) 1,321.99' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-20-11
- 4) 2,643.98' EAST TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 8-20-11
- 5) 1,318.87' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF THE SW1/4 SE1/4 OF SECTION 8-20-11
- 6) 2,637.74' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 8-20-11

CENTER CORNER 08-20-11