

**WEST 1/16<sup>TH</sup> CORNER NORTHEAST QUARTER OF SECTION 08, TOWNSHIP 20 SOUTH,  
RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 58 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 155 DATED FEBRUARY 15, 1872 TO ESTABLISH THE CORNERS TO THE SOUTH 1/4 OF THE NORTHEAST 1/4 OF SECTION 8-20-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/2 CORNER OF THE NORTHEAST 1/4 OF SECTION 8-20-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-20-11 AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-20-11 ON THIS **PERMANENT SURVEY**.

**HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:**

- 1) 1,316-1/2' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-20-11
- 2) 1,316-1/2' SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 8-20-11
- 2) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 18, 2002, FOR PROJECT NUMBER 01406-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE SOUTHEAST QUARTER AND THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 8-20-11, SAID THAT SHE SET THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 8-20-11 ON LINE AND AT HALF THE DISTANCE BETWEEN THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 8-20-11. **SHE DETERMINED THAT THE TRUE POSITION FELL IN A CORNER FENCE POST AT THE INTERSECTION OF FENCES.**
- 1) FELL IN HEDGE CORNER POST FOR FENCES TO THE EAST-WEST AND NORTH-SOUTH
- 2) 67.30' WSW TO A 40 D NAIL & BOTTLE CAP IN THE EAST FACE OF A POWER TRANSMISSION POLE
- 3) **10.0' SOUTH TO A 1/2" REBAR WITH HER "LS 1130" CAP SET AS A WITNESS**
- 4) **10.0' EAST TO A 1/2" REBAR WITH HER "LS 1130" CAP SET AS A WITNESS**
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,314.00' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 8-20-11
- 2) 1,314.00' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 8-20-11
- 3) 2,630.87' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 8-20-11
- 4) 3,951.74 SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 8-20-11
- 5) 2,640.80' EAST TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 8-20-11

WEST SIXTEENTH CORNER NORTHEAST QUARTER 08-20-11