

**WEST 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER OF SECTION 08, TOWNSHIP 20 SOUTH,  
RANGE 11 EAST**

1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 18, 2002, FOR PROJECT NUMBER 01406-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE SOUTHEAST QUARTER AND THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 8-20-11, SAID THAT **SHE SET A 1/2" REBAR WITH HER "LS 1130" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 8-20-11 ON LINE AND AT HALF THE DISTANCE BETWEEN THE CENTER CORNER AND THE SOUTH 1/4 CORNER OF SECTION 8-20-11.

- 1) 6.0' WEST TO A FENCE RUNNING NORTH-SOUTH
- 2) 47.10' NW TO A CONCRETE NAIL & BOTTLE CAP IN A TIE POST
- 3) 13.70' SW TO A CONCRETE NAIL & BOTTLE CAP IN A TIE POST
- 4) 11.90' NORTH TO A TIE POST

**HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,318.87' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 8-20-11
- 2) 1,318.87' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 8-20-11
- 3) 2,632.87' NORTH TO THE CORNER FENCE POST SHE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 8-20-11 AS REFERENCED BY TWO 1/2" REBARS WITH HER "LS 1130" CAPS SET AS WITNESSES
- 4) 3,946.87' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 8-20-11
- 5) 1,320.29' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF THE SW1/4 SE1/4 OF SECTION 8-20-11
- 6) 2,640.58' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 8-20-11

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 08-20-11