

NORTH 1/4 CORNER SECTION 09, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 399 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.97 CHAINS WEST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-11
 - 2) 39.97 CHAINS EAST TO THE 20" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 208 AND DATED JUNE 1872, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 9-20-11 ON THIS **PERMANENT SURVEY**.

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 DATED MARCH 25-31, 1902 ORDERED BY CHARLES EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4, THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE EAST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 3-20-11, AND WILL RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE ON LINE WITH FENCES** AT THE NORTH 1/4 CORNER OF SECTION 9-20-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.06-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-20-11
 - 2) 40.06-1/2 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 3-20-11
 - 3) 79.96-1/2 CHAINS EAST TO THE 18" X 4" X 4" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 3-20-11
 - 4) 120.24-1/2 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 3-20-1
 - 5) 279.91-1/2 CHAINS EAST TO THE TOWNSHIP LINE – NO STONE

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED MARCH 9, 2001, FOR PROJECT NUMBER 01073-02, SURVEY F04002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A 96.43 ACRE TRACT OF LAND LOCATED IN THE SOUTHWEST QUARTER AND THE SOUTHEAST QUARTER OF SECTION 4-20-11, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 4-20-11 WAS **OBLITERATED**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 4-20-11 IN LINE WITH THE FENCE TO THE SOUTH, ACCORDING TO A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 226 BY ALVA J. SMITH IN 1902.
 - 1) 19.7' NORTH TO A PK NAIL & WASHER IN A GATE POST
 - 2) 20.4' SOUTH TO A PK NAIL & WASHER IN A CORNER GATE POST
 - 3) 38.6' SE TO A PK NAIL & WASHER IN THE EAST GATE POST
 - 4) 20' SOUTH TO A LINE OF FENCE TO THE WEST
 - 5) 20' NORTH TO A LINE OF FENCE EAST-WEST
 - 6) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD EAST-WEST

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,355.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 96.43 ACRE TRACT
 - 2) 2,641.34' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 4-20-11
 - 3) 1,651.43' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 96.43 ACRE TRACT
 - 4) 2,641.43' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4-20-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F04003 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR FIVE TRACTS IN THE WEST HALF OF THE FRACTIONAL NORTHWEST QUARTER OF SECTION 4-20-11 FOR PROJECT NUMBER 02157-02 DATED JULY 26, 2002, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 4-20-11 FROM A PRIOR SURVEY. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,641.43' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-20-11
- 2) 2,641.43' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF SECTION 4-20-11
- 3) 2,636.33' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 4-20-11
- 4) 5,265.59' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 4-20-11 ON THE TOWNSHIP LINE

NORTH QUARTER CORNER 09-20-11