

WEST 1/4 CORNER SECTION 09, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 398 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 22" X 16" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 9-20-11 ON JULY 2, 1857.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-11
 - 2) 40.00 CHAINS SOUTH TO THE 28" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-20-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 58 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 155 DATED FEBRUARY 15, 1872 TO ESTABLISH THE CORNERS TO THE SOUTH 1/4 OF THE NORTHEAST 1/4 OF SECTION 8-20-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 8-20-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,319-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 8-20-11
 - 2) 2,639' NORTH TO THE STONE FOUND AT THE NORTHEAST CORNER OF SECTION 8-20-11

- 3) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE DATED JANUARY 31, 1997, FOR JOB NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREAS, SAID THAT SHE CONSIDERED THAT THE WEST 1/4 CORNER OF SECTION 9-20-11 WAS **LOST**. **SHE SET A 1/2" REBAR WITH A "LS 82" CAP** FOR THE WEST 1/4 CORNER OF SECTION 9-20-11.
 - 1) 8.0' NORTH TO A LINE OF HEDGE TO THE WEST
 - 2) 6.4' NORTH TO A LINE OF FENCE TO THE EAST
 - 3) 26.5' EAST TO A LINE OF FENCE TO THE SOUTH
 - 4) 22.5' EAST TO A LINE OF FENCE TO THE NORTH

- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE DATED SEPTEMBER 18, 2002, FOR PROJECT NUMBER 01406-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE SOUTHEAST QUARTER AND THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 8-20-11, SAID THAT **SHE FOUND THE 1/2" REBAR WITH A "LS 82" CAP** AT THE EAST 1/4 CORNER OF SECTION 8-20-11 FROM HER EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JANUARY 31, 1997.
 - 1) 6.50' NORTH TO A FENCE LINE TO THE EAST
 - 2) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "J"
 - 3) 25.0' SOUTH TO A FENCE LINE TO THE WEST
 - 4) 20.0' WEST TO A 1/2" REBAR WITH HER CAP
 - 5) 26.25' EAST TO A CONCRETE NAIL & BOTTLE CAP IN THE SOUTH BRACE POST
 - 6) 33.40' SW TO A BOLT IN THE EAST FACE OF A CORNER FENCE POST
 - 7) 3.0' NORTH TO A LINE OF HEDGE TO THE WESTHER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,317.43' NORTH TO THE 1/2" REBAR WITH "LS 82" CAP SHE FOUND AT THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 8-20-11
 - 2) 1,317.15' SOUTH TO THE THEORETICAL POSITION FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 8-20-11
 - 3) 2,634.30' SOUTH TO THE COTTON GIN SPINDLE SHE SET OVER A CORRUGATED METAL PIPE CULVERT FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-20-11

HER INFORMATION IS CONTINUED ON PAGE 2

- 4) 1,321.99' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8-20-11
- 5) 2,643.98' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 8-20-11

WEST QUARTER CORNER 09-20-11