

WEST 1/4 CORNER SECTION 10, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 395 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 13" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 10-20-11.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 111 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 33 DATED JUNE 18, 1873 TO ESTABLISH THE CENTER CORNER OF SECTION 10-20-11 AND TO ESTABLISH THE CORNERS COMMON TO THE EAST 1/2 OF THE EAST 1/2 OF THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 10-20-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,314' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 10-20-11
 - 2) 1,971' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4/4 CORNER OF THE SW1/4 OF SECTION 10-20-11
 - 3) 2,628' EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 10-20-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 DATED MARCH 25-31, 1902 ORDERED BY CHARLES EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4, THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE EAST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 3-20-11, AND WILL RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-20-11 AS HE RAN THE SECTION LINES FROM THE STAKE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 10-20-11 NORTH TO THE STAKE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 3-20-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 4) JAMES H. BROSEMER, L.S. 82, KDOT CHIEF OF SURVEYS, FOR KDOT PROJECT 57-56-K0548-01, IN 1981, SAID THAT HE EXCAVATED WITH HAND TOOLS FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-20-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" REBAR WITH AN ALUMINUM KDOT CAP STAMPED "W1/4 10-20-11"** FOR THE WEST 1/4 CORNER OF SECTION 10-20-11 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER; I.E., IN LINE WITH A HEDGE TO THE EAST AND A FENCE TO THE WEST, AND 25' WEST OF A LINE OF HEDGE TO THE NORTH, AND IN THE TRAVELED WAY OF AN OLD ROAD SCAR NORTH AND SOUTH.
 - 1) 18.15' EAST TO A SPIKE & KDOT WASHER IN A RAILROAD TIE FENCE POST
 - 2) 24.8' NE TO A SPIKE & KDOT WASHER IN A 10" HEDGE TREE
 - 3) 42.0' WEST TO THE CENTERLINE AT THE TOP OF A 4" STEEL WATER LINE MARKER POST

WEST QUARTER CORNER 10-20-11