

NORTH 1/4 CORNER SECTION 11, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 391 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 16" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 11-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 21" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-20-11
 - 2) 40.00 CHAINS EAST TO THE 21" X 11" X 6" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-20-11

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 DATED MARCH 25-31, 1902 ORDERED BY CHARLES EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4, THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE EAST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 3-20-11, AND WILL RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 11-20-11 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-20-11 EAST TO THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

NORTH QUARTER CORNER 11-20-11