

CENTER CORNER OF SECTION 12, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 75, A **PERMANENT SURVEY** AT THE REQUEST OF W. C. LONG RECORDED IN SURVEY BOOK "F" ON PAGE 155 DATED JUNE 16 & 17, 1903, FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF SECTION 12-20-11, AND THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SAID SECTION 12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND A STONE AT THE INTERSECTION OF HEDGES NEAR THE CENTER CORNER OF SECTION 12-20-11 ON THIS PERMANENT SURVEY**. HE SAID THAT AFTER HE RAN THE LINES FROM THE OPPOSITE 1/4 CORNER HE DETERMINED THAT THE **"TRUE CENTER CORNER"** WAS **3 LINKS SOUTH OF THE STONE**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 172 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 162" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00-1/2 CHAINS NORTH BY HIS SURVEY NOTES TO THE 16" X 9" X 4" STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NE1/4 OF SECTION 12-20-11 [20.16 CHAINS ON HIS SURVEY DRAWING]
- 2) 40.03 CHAINS NORTH BY HIS SURVEY NOTES TO THE 14" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 12-20-11 ON TRANSIT LINE AND HALFWAY BETWEEN THE STONES THAT HE SET FOR THE PERMANENT OPPOSITE SECTION CORNERS [40.32 CHAINS ON HIS SURVEY DRAWING]

NOTE: HIS SURVEY NOTES SAID THAT THE DISTANCE FROM THE TRUE CENTER CORNER OF SECTION 12-20-11 TO THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 12-20-11 WAS **40.03 CHAINS** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

CENTER CORNER 12-20-11