

**WEST 1/16<sup>TH</sup> CORNER NORTHEAST QUARTER OF SECTION 12, TOWNSHIP 20 SOUTH,  
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 75, A **PERMANENT SURVEY** AT THE REQUEST OF W. C. LONG RECORDED IN SURVEY BOOK "F" ON PAGE 155 DATED JUNE 16 & 17, 1903, FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF SECTION 12-20-11, AND THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SAID SECTION 12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 16" X 9" X 4" STONE** FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 12-20-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 12-20-11 AND THE TRUE CENTER CORNER OF SECTION 12-20-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 172 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 162" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 20.0-1/2 CHAINS NORTH BY HIS SURVEY NOTES TO THE 14" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 12-20-11 ON TRANSIT LINE AND HALFWAY BETWEEN THE STONES HE SET FOR THE PERMANENT SECTION CORNERS [20.16 CHAINS ON HIS SURVEY DRAWING]
- 2) 20.00-1/2 CHAINS SOUTH BY HIS SURVEY NOTES TO THE TRUE CENTER CORNER OF SECTION 12-20-11 THAT IS 3 LINKS SOUTH OF A STONE THAT HE FOUND IN A HEDGE [20.16 CHAINS ON HIS SURVEY DRAWING.
- 3) **NOTE:** THE TOTAL DISTANCE BETWEEN THE TRUE CENTER CORNER AND THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 12-20-11 IS **40.03 CHAINS** BY HIS SURVEY NOTES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

WEST SIXTEENTH CORNER NORTHEAST QUARTER 12-20-11