

**NORTH 1/4 CORNER SECTION 16, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 398 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 13" X \_\_\_** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-20-11 ON JUNE 28, 1857. **[NOTE: THE THIRD DIMENSION IS NOT LISTED IN THE GLO NOTES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**  
**THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**
  - 1) 39.95 CHAINS WEST TO THE 28" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-20-11
  - 2) 79.90 CHAINS EAST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-20-11
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 60 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 208 DATED JUNE 21, 1872 TO SUBDIVIDE THE EAST 1/2 OF THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4 BY A LINE RUNNING EAST & WEST, AND ALSO TO ESTABLISH THE CORNERS OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 16-20-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 16-20-11 ON THIS **PERMANENT SURVEY.**  
**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 1,317' SOUTH TO THE POST HE SET FOR THE TEMPORARY WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 16-20-11
  - 2) 2,634' SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 16-20-11

NORTH QUARTER CORNER 16-20-11