

WEST 1/4 CORNER SECTION 17, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 403 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 28" X 12" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 18-20-11.

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 10, 2006, FOR PROJECT NUMBER 06293-02, SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR LYON COUNTY PROJECT NUMBER 06-KU, THE REPLACEMENT OF BRIDGE 957.5-532.0, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 18-20-11, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 18-20-11 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER; IN LINE WITH A FENCE TO THE WEST AND IN THE CENTER OF COUNTY ROAD "H".
 - 1) 19.65' WEST TO A CONCRETE NAIL & WASHER IN A CORNER POST
 - 2) 25.55' WSW TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
 - 3) 24.75' WNW TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
 - 4) IN LINE WITH A FENCE TO THE WEST EXTENDED
 - 5) IN THE CENTERLINE TRAVELED-WAY FOR COUNTY ROAD "H"

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,634.15' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 18-20-11 AT PROJECT STATION 52+75.32
 - 2) 5,268.30' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-20-11

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 9, 2008 FOR PROJECT NUMBER 08278-02, SURVEY F18002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 18-20-11 FOR DONNA WILLIAMS, SAID THAT **HE FOUND THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP** AT THE EAST 1/4 CORNER OF SECTION 18-20-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED NOVEMBER 10, 2006.
 - 1) 19.65' WEST TO A CONCRETE NAIL & WASHER IN A CORNER POST
 - 2) 25.55' WSW TO A 40 D NAIL & WASHER IN A STEEL FENCE POST
 - 3) 24.75' WNW TO A 40 D NAIL & WASHER IN A STEEL FENCE POST
 - 4) IN A LINE OF FENCE TO THE WEST EXTENDED
 - 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H"

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,636.21' WEST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 18-20-11
 - 2) 3,954.22' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 18-20-11
 - 3) 5,278.48' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 18-20-11 ON THE RANGE LINE
 - 4) 2,634.08' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 18-20-11
 - 5) 2,638.61' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 18-20-11

WEST QUARTER CORNER 17-20-11