

**NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 18, TOWNSHIP 20 SOUTH,
RANGE 11 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED DECEMBER 9, 2008 FOR PROJECT NUMBER 08278-02, SURVEY F18002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 18-20-11 FOR DONNA WILLIAMS, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 18-20-11 AT THE GLO PROPORTIONATE DISTANCE AND ON LINE BETWEEN THE NORTHWEST CORNER AND THE NORTH QUARTER CORNER OF SECTION 18-20-10.

- 1) 24.75' SOUTH TO A 1/2" REBAR WITH HIS "LS 752" CAP [**HORIZONTAL TIE**]
- 2) 191.80' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP [**HORIZONTAL TIE**]
- 3) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 110
- 4) 33.20' NNE TO A 40 D NAIL & WASHER IN A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.22' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-20-11
- 2) 1,317.30' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-20-11
- 3) 3,952.06' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 18-20-11
- 4) 24.75' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET ON THE SOUTH RIGHT-OF-WAY LINE OF COUNTY ROAD 110
- 5) 1,317.17' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 18-20-11
- 6) 2,634.34' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 18-20-11

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 18-20-11