

**NORTH 1/4 CORNER SECTION 19, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 402 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-20-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.10 CHAINS WEST TO THE 23" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-20-11 ON THE RANGE LINE
  - 2) 40.00 CHAINS EAST TO THE 23" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-19-11
  
- 2) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 152  
ON MAY 14, 1965 A PETITION SIGNED BY D. FOX AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 20-11 WAS PRESENTED TO HOWARD E. ENSMINGER, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND W. D. KRETSINGER, COUNTY ENGINEER, ON JUNE 4, 1965 AND THEY RECOMMENDED THAT THE FOLLOWING ROAD BE **VACATED:**
  - 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 19-20-11 AND TERMINATING EAST 1/2 MILE.
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 9, 2008 FOR PROJECT NUMBER 08278-02 AND SURVEY F18002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 18-20-11 FOR DONNA WILLIAMS, SAID THAT HE SEARCHED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 18-20-11, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 18-20-11 BY GLO PROPORTIONATE DISTANCE AND ON LINE BETWEEN THE SOUTHEAST CORNER AND THE SOUTHWEST CORNER OF SECTION 18-20-11.
  - 1) 6.80' SE TO A 40 D NAIL & WASHER IN A BRACE POST
  - 2) 4.30' SOUTH TO A LINE OF FENCE RUNNING EAST AND WEST
  - 3) 9.40' SSW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
  - 4) 7.0' WEST TO A LINE OF FENCE TO THE SOUTH EXTENDED
  - 5) 18.40' SW TO A 40 D NAIL & WASHER IN A BRACE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,645.49' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-20-11 ON THE RANGE LINE
  - 2) 2,638.88' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 18-20-11
  - 3) 2,635.58' NORTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 18-20-11
  - 4) 3,952.71' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 18-20-11
  - 5) 5,269.83' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-20-11

NORTH QUARTER CORNER 19-20-11