

NORTHWEST CORNER SECTION 20, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 401 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 10" X 4"** FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-20-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.90 CHAINS EAST TO THE 24" X 8" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-20-11
- 2) 79.80 CHAINS EAST TO THE 19" X 13" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-20-11

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 34 DATED SEPTEMBER 26, 1882, FOR A ROAD IN TOWNSHIP 20, RANGES 10 & 11 FOR WILLIAM STEPHEN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-20-11 AT THE TERMINUS OF THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 23-20-10; THENCE CONTINUES WEST ON THE SECTION LINE FOR 45 CHAINS AT AN ANGLE AT N. 69° W. FOR 3.50 CHAINS TO A POINT; THENCE S. 62°15' W. FOR 6.00 CHAINS TO INTERSECT THE SECTION LINES; THENCE WEST ON THE SECTION LINES FOR 26.24 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-20-10; THENCE CONTINUES WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-20-10 TO COMMENCE THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, A ROAD SURVEY FOR ROAD NUMBER 192 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 354 TO 356 PETITIONED BY WILLIAM STEPHEN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-10 & 20-11 [PACKET 402 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 26, 1882, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 11, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 25, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-20-10 AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 23-20-10; THENCE CONTINUES WEST ON THE SECTION LINE FOR 45 CHAINS AT AN ANGLE AT N. 69° W. FOR 3.50 CHAINS TO A POINT; THENCE S. 62°15' W. FOR 6.00 CHAINS TO INTERSECT THE SECTION LINES; THENCE WEST ON THE SECTION LINES FOR 26.24 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-20-10; THENCE CONTINUES WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-20-10 TO COMMENCE THIS ROAD SURVEY

- 4) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 83 AND DATED DECEMBER 20, 1883 FOR A ROAD IN TOWNSHIP 20, RANGE 11 FOR CHARLES COWAN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 18-20-11 AT THE TERMINUS OF THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2.2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-11 TO COMMENCE THIS ROAD SURVEY

- 5) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 237 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 534 TO 536 PETITIONED BY CHARLES COWAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-11 [PACKET 484 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 20, 1883, AND WAS ESTABLISHED AT 40 FOOT WIDE ON JANUARY 11, 1884 AS NOTED BY P. Y HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 28, 1884 BY R. LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 18-20-11 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2.2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-11 TO COMMENCE THIS ROAD SURVEY

- 6) STEVEN S. BROSEMER, L.S. 752, APPOINTED COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 TO PERMANENTLY ESTABLISH THE EAST LINE OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 29-20-11 PETITIONED BY BEVERLY CROOK THAT BEGAN ON SEPTEMBER 21, 1983 AND CONTINUED UNTIL COMPLETION ON SEPTEMBER 26, 1983, SAID THAT HE SEARCHED WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 20-20-11. HE USED A SPLIT OF THE RIGHT-OF-WAY FENCES TO THE WEST TO DETERMINE A **THEORETICAL POSITION** FOR THE NORTHWEST CORNER OF SECTION 20-20-1, BUT THE POSITION WAS NOT MONUMENTED ON THIS **PERMANENT SURVEY**. SEE ALSO SURVEY F29006 IN THE SURVEY FILE FOR TOWNSHIP 20-11 RECORDED IN VOLUME 403 ON PAGE 641 IN THE REGISTER OF DEEDS OFFICE FOR A COPY OF THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640.5' SOUTH TO THE THEORETICAL POSITION FOR THE WEST 1/4 CORNER OF SECTION 20-20-11, AS EVIDENCED BY A LINE OF FENCE TO THE EAST AND A LINE OF HEDGE TO THE WEST
 - 2) 5,281.0' SOUTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-20-11
 - 3) 7,921.5' SOUTH TO THE #4 REBAR HE FOUND AND HE ACCEPTED FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-20-11
 - 4) 10,561.15' SOUTH TO THE #4 REBAR HE FOUND AND HE ACCEPTED FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29
 - 5) 13,202.15' SOUTH TO THE THEORETICAL POSITION FOR THE WEST 1/4 CORNER OF SECTION 32-20-11 AT A LINE OF FENCE TO THE WEST

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 9, 2008 FOR PROJECT NUMBER 08278-02 AND SURVEY F18002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 18-20-11 FOR DONNA WILLIAMS, SAID THAT HE HAD SEARCHED FOR THE STONE AT THE SOUTHEAST CORNER OF SECTION 18-20-11 FROM THE SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE IN 1983. HE DEEMED THAT THIS CORNER WAS OBLITERATED. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTHEAST CORNER OF SECTION 18-20-11 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER.

HIS TIES ARE ON PAGE 3

- 1) 23.90' WEST TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 2) 24.85' WSW TO A 40 D NAIL & WASHER IN THE SOUTH GATE POST
- 3) 44.45' SE TO A 40 D NAIL & WASHER IN THE SOUTH GATE POST
- 4) IN LINE WITH A FENCE TO THE WEST – EXTENDED
- 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD “H” NORTH-SOUTH
- 6) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 100 TO THE EAST – EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,638.88' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 18-20-11
- 2) 5,284.37' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-20-11 ON THE RANGE LINE
- 3) 2,638.61' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-20-11
- 4) 5,272.69' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 18-20-11

NORTHWEST CORNER 20-20-11