

NORTHWEST CORNER SECTION 22, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 393 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 13" X 2-1/2"** FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.14 CHAINS EAST TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-20-11
 - 2) 80.27 CHAINS EAST TO THE 21" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-20-11

- 2) IN ROAD RECORD BOOK "A" ON PAGES 190 TO 192, [PACKET 178 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THE BOARD OF COUNTY COMMISSIONERS MET ON JULY 17, 1871 AND APPOINTED COMMISSIONERS H. V. BENNETT CHAIRMAN AND FLAGMAN, SAMUEL BROOKOVER AS SECRETARY AND MARKER, AND MILTON CHAMNESS AS CHAINMAN, AND EMPLOYED W. B. GODFREY AS SURVEYOR FOR THE STATE ROAD FROM EMPORIA IN LYON COUNTY TO EUREKA IN GREENWOOD COUNTY THAT WAS COMPLETED ON JULY 20, 1871. DANIEL S. GILMORE, COUNTY CLERK, NOTED THAT THE REPORT WAS ACCEPTED AND PLACED IN THE FILE, AND THE ROAD WAS ORDERED OPENED AT 64 FEET WIDE, AND RECORDED, ACCORDING TO THE PLAT AND SURVEY BY THE BOARD OF COUNTY COMMISSIONERS ON NOVEMBER 10, 1871. THE SURVEY NOTES AND DRAWING INDICATE THE ROAD PASSES THROUGH THE NORTHWEST CORNER OF SECTION 22-20-11 ON THIS STATE ROAD.
THE SURVEY DRAWING/NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS STATE ROAD EXTENDS NORTH ON THE SECTION LINES AT A TURN TO THE NORTHEASTERLY IN THE SW1/4 OF SECTION 15-20-11
 - 2) THIS STATE ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE WEST 1/4 CORNER OF SECTION 27-20-11

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 170 DATED AUGUST 20, 1877 TO ESTABLISH THE EAST 1/4 SECTION CORNER OF SECTION 16-20-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 16-20-11 ON THIS **PERMANENT SURVEY**.

- 4) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 83 AND DATED DECEMBER 20, 1883 FOR A ROAD IN TOWNSHIP 20, RANGE 11 FOR CHARLES COWAN, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 16-20-11 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 18-20-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-11 TO COMMENCE THIS ROAD SURVEY

- 5) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 237 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 534 TO 536 PETITIONED BY CHARLES COWAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-11 [PACKET 484 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 20, 1883, AND WAS ESTABLISHED AT 40 FOOT WIDE ON JANUARY 11, 1884 AS NOTED BY P. Y HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 28, 1884 BY R.

LARKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 16-20-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 18-20-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-11 TO COMMENCE THIS ROAD SURVEY
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 226 AND DATED MARCH 1902, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 22-20-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 85" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-11 SHOWS AN **IRON PIN** AT THE "NE CORNER SECTION 21-20-11".
- 1) 27' SE TO A CORNER FENCE POST
 - 2) 47' SW TO A CORNER FENCE POST
 - 3) 26.5' NW TO A CORNER FENCE POST
- 8) DOUGLAS A. FARRAR, L.S. 720, OF SHAFER, KLINE & WARREN, INC., IN A LAND SURVEY REFERENCE REPORT DATED JULY 7, 2005, FOR JOB NUMBER 104753, SAID THAT **HE FOUND A 1/2" IRON BAR AT 1 FOOT DEEP** AT THE NORTHEAST CORNER OF SECTION 21-20-11 RECOVERED FROM OLD REFERENCE TIES. HE SENT THE FOLLOWING **HORIZONTAL TIES:**
- 1) 36.70' SOUTHWEST TO A MAG NAIL & SHINER HE SET IN THE WEST SIDE OF A CORNER FENCE POST
 - 2) 45.79' SOUTHEAST TO A MAG NAIL & SHINER HE SET IN THE WEST SIDE OF A POWER POLE
 - 3) 51.77' NORTHEAST TO A MAG NAIL & SHINER HE SET IN THE NORTHWEST SIDE OF A POWER POLE
 - 4) 42.36' NORTHWEST TO A MAG NAIL & SHINER HE SET IN THE SOUTH SIDE OF A P. I. FENCE POST
 - 5) IN THE CENTERLINE OF THE INTERSECTION OF THE COUNTY ROADS
 - 6) **AN EXISTING PK NAIL IS 1.4' SOUTH AND 0.7' WEST**

NORTHWEST CORNER 22-20-11