

NORTH 1/4 CORNER SECTION 23, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 390 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.10 CHAINS WEST TO THE 21" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-20-11
 - 2) 40.09 CHAINS EAST TO THE 30" X 18" X 3-1/2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-20-11

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 57, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 55 DATED JUNE 23, 1870 TO ESTABLISH THE CENTER OF THE SOUTHWEST 1/4 OF SECTION 14-20-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 14-20-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.98-1/2 CHAINS WEST TO THE POST HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 14-20-11
 - 2) 39.97 CHAINS WEST TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 14-20-11
 - 3) 19.92 CHAINS NORTH TO THE POST THAT HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 14-20-11
 - 4) 39.84 CHAINS NORTH TO THE STONE THAT HE FOUND AT THE CENTER CORNER OF SECTION 14-20-11

- 3) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 63 AND DATED AUGUST 1870, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 23-20-11 ON THIS **PERMANENT SURVEY**.

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 28, 2010 FOR PROJECT NUMBER 10097-02, SURVEY F14002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A 7.92 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 14-20-11 FOR HOYT SCHAEFER, SAID THAT HE SEARCHED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 14-20-11, BUT THE STONE WAS **NOT** FOUND DUE TO A ROCK LEDGE AT 30" DEEP. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 14-20-11 ON LINE BETWEEN THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 14-20-11, AND ON LINE WITH A FENCE TO THE NORTH.
 - 1) IN LINE WITH A FENCE TO THE NORTH
 - 2) 31.9' NE TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 3) 20.3' SE TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 4) 13.95' SOUTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 3.0' NORTH TO THE TRAVELED WAY OF DIRT COUNTY ROAD 100 EAST-WEST
 - 6) 14' SOUTH TO A LINE OF FENCE TO THE WEST
 - 7) 16' SOUTH TO A LINE OF FENCE TO THE EASTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,643.32' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 14-20-11
 - 2) 2,648.04' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 14-20-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,638.17' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 14-20-11
- 4) 4,442.60' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET IN THE CENTERLINE OF COUNTY ROAD "L5" AS BUILT
- 5) 5,274.60' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 14-20-11, AND THE NORTHWEST CORNER OF THE 7.92 ACRE TRACT

NORTH QUARTER CORNER 23-20-11