

**CENTER CORNER OF SECTION 24, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) BRAD C. ZILLOX, P.S. 889, OF LANDPLAN ENGINEERING, P.A., IN A LAND SURVEY REFERENCE REPORT DATED MAY 14, 2015 FOR PROJECT NUMBER 20151017 FOR AN ALTA/ACSM SURVEY FOR ANSON LAND HOLDING OF THE NORTHWEST 1/4 AND THE NORTH HALF OF THE SOUTHWEST 1/4 AND THE NORTH 120 ACRES OF THE NORTHEAST 1/4 OF SECTION 24-20-11, LARGE SURVEY NUMBER SR #24001 IN THE SURVEY DRAWER FOR TOWNSHIP 20-11, SAID THAT THE CENTER CORNER OF SECTION 24-20-11 FALLS IN A TREE. **HE CALCULATED** THE CENTER CORNER OF SECTION 24-20-11 BY CROSSING OUT TH QUARTER CORNERS. HE SENT THE FOLLOWING **HORIZONTAL TIES**:
- 1) **5.00' NORTH TO THE 5/8" X 24" BAR WITH HIS "PS 889" CAP SET AS A TIE TO THE CENTER OF THE SECTION ON THE QUARTER SECTION LINE**
  - 2) **5.00' EAST TO THE 5/8" X 24" BAR WITH HIS "PS 889" CAP SET AS A TIE TO THE CENTER OF THE SECTION ON TH QUARTER SECTION LINE**
  - 3) THE CENTER OF THE SECTION FALLS IN LINE WITH A NORTH-SOUTH FENCE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 659.48' NORTH TO THE CALCULATED POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE S1/2 OF THE NE1/4 OF SECTION 24-20-11
  - 2) 2,643.12' WEST TO THE 1/2" X 24" IRON BAR WITH HIS "PLS 889" CAP HE DRILLED INTO THE FRACTURED STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 24-20-11
  - 3) 2,645.04' FEET EAST TO THE 5/8" X 24" IRON BAR WITH HIS "PLS 889" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 24-20-11
  - 4) 1,320.46' SOUTH TO THE 5/8" X 24" IRON BAR WITH HIS "PLS 889" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 24-20-11
  - 5) 2,640.91' SOUTH TO THE 5/8" X 30" IRON BAR WITH HIS "PLS 889" CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 24-20-11

CENTER CORNER 24-20-11