

WEST 1/4 CORNER SECTION 24, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 386 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 19" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 24-20-11 ON JUNE 25, 1857. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 30" X 18" X 3-1/2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-20-11
 - 2) 40.00 CHAINS SOUTH TO THE 22" X 17" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-20-11

- 2) BRAD C. ZILLOX, P.S. 889, OF LANDPLAN ENGINEERING, P.A., IN A LAND SURVEY REFERENCE REPORT DATED MAY 14, 2015 FOR PROJECT NUMBER 20151017 FOR AN ALTA/ACSM SURVEY FOR ANSON LAND HOLDING OF THE NORTHWEST 1/4 AND THE NORTH HALF OF THE SOUTHWEST 1/4 AND THE NORTH 120 ACRES OF THE NORTHEAST 1/4 OF SECTION 24-20-11, LARGE SURVEY NUMBER SR #24001 IN THE SURVEY DRAWER FOR TOWNSHIP 20-11, SAID THAT THEY EXCAVATED FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 24-20-11 WITH A LYON COUNTY BACKHOE. **THEY FRACTURED THE STONE THAT THEY FOUND JUST BELOW THE SURFACE THAT MATCHED THE GLO STONE DIMENSIONS. THEY DRILLED A HOLE THROUGH THE CENTER MASS OF THE STONE AND THEY SET A REBAR WITH "PLS 889" CAP FOR THE WEST 1/4 CORNER OF SECTION 24-20-11. HE SENT THE FOLLOWING HORIZONTAL TIES:**
 - 1) 60.20' SOUTH-SOUTHEAST TO THE 60 D MAG NUB SET IN THE SOUTHWEST FACE OF A CORNER FENCE POST
 - 2) 30.60' SOUTHWEST TO THE 60 D MAG HUB SET IN THE NORTHWEST FACE OF A POWER POLE
 - 3) 22.50' NORTHWEST TO THE TOP CENTER OF THE CULVERT [NORTH END] GOING UNDER A FIELD ENTRANCE
 - 4) 1.5' ± WEST TO THE CENTERLINE OF THE TRAVEL WAY ON COUNTY ROAD "M" HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,322.20' SOUTH TO THE 5/8" X 24" IRON BAR WITH HIS "PLS 889" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 24-20-11
 - 2) 2,644.40' SOUTH TO THE 5/8" IRON BAR WITH AN ILLEGIBLE RED CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 24-20-11
 - 3) 2,644.23' NORTH TO THE 5/8" IRON BAR WITH A RED LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-20-11
 - 4) 2,643.12' EAST TO THE CENTER CORNER OF SECTION 24-20-11 THAT FALLS ON A TREE. HE SET TWO 5/8" X 24" IRON BARS WITH HIS "PLS 889" CAPS AS REFERENCE POINTS 5' NORTH ON THE QUARTER SECTION LINE AND 5' EAST ON THE QUARTER SECTION LINE
 - 5) 5,288.16' EAST TO THE 5/8" X 24" IRON BAR WITH HIS "PLS 889" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 24-20-11 ON THE RANGE LINE

WEST QUARTER CORNER 24-20-11