

NORTH 1/4 CORNER SECTION 25, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 385 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 20" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 24 & 25-20-11 ON JUNE 25, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.06 CHAINS WEST TO THE 22" X 17" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-20-11
 - 2) 40.05 CHAINS EAST TO THE 18" X 14" X 4-1/2" LIMESTONE HE SET FOR THE CORNER TO SECTIONS 24 & 25-20-11 ON THE EAST TOWNSHIP BOUNDARY

- 2) BRAD C. ZILLOX, P.S. 889, OF LANDPLAN ENGINEERING, P.A., IN A LAND SURVEY REFERENCE REPORT DATED MAY 14, 2015 FOR PROJECT NUMBER 20151017 FOR AN ALTA/ACSM SURVEY FOR ANSON LAND HOLDING OF THE NORTHWEST 1/4 AND THE NORTH HALF OF THE SOUTHWEST 1/4 AND THE NORTH 120 ACRES OF THE NORTHEAST 1/4 OF SECTION 24-20-11, LARGE SURVEY NUMBER SR #24001 IN THE SURVEY DRAWER FOR TOWNSHIP 20-11, SAID THAT THEY EXCAVATED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 24-20-11, BUT THE STONE WAS **NOT** FOUND. HE DETERMINED THAT THIS CORNER WAS **OBLITERATED**. HE **RESET** THIS CORNER USING GLO PRORATION. **HE SET A 5/8" X 30" BAR WITH HIS "PS 889" CAP SET 0.50' BELOW GRADE** FOR THE SOUTH 1/4 CORNER OF SECTION 24-20-11. HE SENT THE FOLLOWING **HORIZONTAL TIES:**
 - 1) 17.02' SOUTH TO THE TOP CENTER [EAST END] OF THE STEEL PIPE UNDER A FIELD ENTRANCE
 - 2) 24.71' SOUTHWEST TO THE TOP CENTER [WEST END] OF THE STEEL PIPE UNDER A FIELD ENTRANCE
 - 3) 15.87' NORTH-NORTHWEST TO THE TOP CENTER [WEST END] OF THE STEEL PIPE UNDER A FIELD ENTRANCE
 - 4) 17.68' NORTH-NORTHEAST TO THE TOP CENTER [EAST END] OF THE STEEL PIPE UNDER A FIELD ENTRANCE
 - 5) 1.5' ± SOUTH OT THE CENTERLINE OF TRAVEL WAY OF COUNTY ROAD 90HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,649.11' WEST TO THE 5/8" IRON BAR WITH AN ILLEGIBLE RED CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 24-20-11
 - 2) 2,649.11' EAST TO THE 5/8" IRON BAR WITH AN ILLEGIBLE YELLOW CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-20-11 ON THE RANGE LINE
 - 3) 1,320.45' NORTH TO THE 5/8" X 24" IRON BAR WITH HIS "PLS 889" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 24-20-11
 - 4) 2,640.91' NORTH TO THE CENTER CORNER OF SECTION 24-20-10 THAT FALLS ON A TREE WITH TWO 5/8" IRON BARS WITH HIS "PLS 889" CAPS HE SET AS REFERENCE POINTS AT 5' NORTH ON THE QUARTER SECTION LINE AND 5' EAST ON THE QUARTER SECTION LINE
 - 5) 3,300.39' NORTH TO THE CALCULATED POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE S1/2 OF THE NE1/4 OF SECTION 24-20-10

NORTH QUARTER CORNER 25-20-11