

NORTHWEST CORNER SECTION 26, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 389 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 27" X 17" X 5"** FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.96 CHAINS EAST TO THE 27" X 13" X 2" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-20-11
 - 2) 79.92 CHAINS EAST TO THE 22" X 17" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-20-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 298 TO 300 PETITIONED BY GRIFFITH HUGHS AND OTHERS FOR TWO COUNTY ROADS IN TOWNSHIP 20-11 [PACKET 322 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1880, WERE APPROVED AS 40 FEET WIDE ROADS ON JULY 13, 1880, AND WERE RECORDED ON JULY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-20-13 ON THE SECOND SECTION OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS SECOND ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 15-20-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
 - 2) THIS SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-20-11 ON THE 4TH STANDARD PARALLEL TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 182 DATED MARCH 26, 1880, FOR A COUNTY ROAD IN TOWNSHIP 20-11, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-20-11 ON THE SECOND ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS SECOND ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 15-20-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
 - 2) THIS SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-20-11 ON THE 4TH STANDARD PARALLEL TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY.

- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 24 DATED AUGUST 16, 1882, FOR G. W. CALGLAZIER, PRINCIPAL PETITIONER, FOR A ROAD IN TOWNSHIP 20, RANGES 10 & 11, SAID THAT **HE SET A STONE** AT THE NORTHEAST CORNER OF SECTION 27-20-11 ON THIS ROAD SURVEY. THERE WAS NO WIDTH RECORDED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 5 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 25-20-10; THEN EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-21-10 TO COMMENCE THIS ROAD SURVEY

- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 25-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, A ROAD SURVEY FOR ROAD NUMBER 194 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 362 TO 364 PETITIONED BY G. W. CALGLAZIER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-10 AND 20-11 [PACKET 400 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 16, 1882, WAS ESTABLISHED AS A 500 FOOT WIDE ROAD. AND WHERE THERE ARE HEDGES, THE HEDGE SHALL BE THE LINE OF THE ROAD AND ENOUGH SHALL BE LEFT ON THE OTHER SIDE OF THE SECTION LINE TO MAKE 50 FEET, ON OCTOBER 11, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 25, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT HE SET A STONE AT OR NEAR THE NORTHWEST CORNER OF SECTION 26-20-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 3) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 5 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 25-20-10; THEN EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-21-10 TO COMMENCE THIS ROAD SURVEY
 - 4) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 25-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 17, 1988, SAID THAT **HE FOUND A 1/2" REBAR** AT THE SOUTHEAST CORNER OF SECTION 22-20-11.
 - 1) 34.3' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
 - 2) 45.7' NW TO A PK NAIL & WASHER IN THE WEST BRACE POST
 - 3) 50.0' SE TO A PK NAIL & WASHER IN A CORNER FENCE POST
 - 4) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD EAST-WEST
 - 5) 1.5' WEST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD NORTH-SOUTH

NORTHWEST CORNER 26-20-11