

WEST 1/4 CORNER SECTION 26, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 389 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 20" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-20-11.
- 2) JAMES H. BROSEMER, L.S. 82, KDOT CHIEF OF SURVEYS, FOR KDOT PROJECT 57-56-K0548-01, IN 1981, SAID THAT HE EXCAVATED WITH A COUNTY MOTOR GRADER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 27-20-11, BUT HE DID NOT FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" REBAR WITH AN ALUMINUM KDOT CAP STAMPED "E1/4 27-20-11"** FOR THE EAST 1/4 CORNER OF SECTION 27-20-11 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER; I.E., 20.0' WEST OF A LINE OF HEDGE TO THE NORTH AND AT 1/2 THE DISTANCE FROM THE SOUTHEAST CORNER TO THE NORTHEAST CORNER OF SECTION 27-20-11.
 - 1) 28.0' ENE TO A SPIKE & KDOT WASHER IN THE TOP OF A FENCE POST
 - 2) 24.6' EAST TO A SPIKE & KDOT WASHER IN THE TOP OF A FENCE POST
 - 3) 29.2' NE TO A U. S. C. & G. S. BENCHMARK
 - 4) 20.0' EAST TO A LINE OF HEDGE TO THE NORTH

WEST QUARTER CORNER 26-20-11